Rebuttal

Journal Name:	Drinking Water Engineering and Science	
Manuscript Number or original submission:	Dwes-2020-8	
Title of the original Manuscript:	Sustainability characteristics of drinking water supply	
New Title of the Revised Manuscript	Sustainability characteristics of drinking water supply in the Netherlands	
Type of the Article	Research article	
Keywords old manuscript	Systems approach; DPSIR; drinking water supply; local scale; sustainability	
New Keywords of the Revised Manuscript	Systems approach; drinking water supply; local scale; sustainability; the Netherlands	

Dear editorial board,

Herewith we respond to the reviews of the anonymous referees. We hope this rebuttal will provide you a clear overview of our response and the adjustments we propose to make to the original manuscript to meet the referees' remarks.

Kind regards, The authors

#	Referee #1 Comments (Received and published: 21 April 2020)	Authors Comments	Adjustments in new manuscript
	Comments: being a quantitative researcher with exposure to narrative style research, I could not appreciate the content presented.	This paper is part of an interdisciplinary research project on drinking water supply, performed by researchers both with quantitative as well as more qualitative disciplinary backgrounds (water resources management, hydrology, climate change studies, drinking water supply) aiming to contribute to the sustainability of drinking water supply. Additional to the more quantitative research on the hydrological impact of drinking water supply, the researchers also were confronted with the complexity of research on sustainable drinking water supply. This urged us to use a systems approach that allowed combining quantitative and qualitative characteristics. We propose to do this by identifying the most relevant challenges that must be addressed in policy development on sustainable drinking water	In the final paragraph section 1 we have added the following to the aim of the research: This research aims to propose a set of sustainability characteristics that describe the drinking water supply system on a local scale <u>to</u> <u>support policy- and decision- making on</u> <u>sustainable</u> <u>drinking water</u> <u>supply.</u>

#	Referee #1 Comments	Authors Comments	Adjustments in
	(Received and published: 21 April 2020)		new manuscript
		supply, offering policy makers and planners an evidence-based approach for assessing sustainability of drinking water supply from their perspective.	line 115-116
2	The authors allude to an integrated assessment based on system thinking for the first time but only stick to DPSIR framework without motivating its choice. There were mentions of socioecological and sociotechnical systems but I didnt see much content coming out from those respective disciplines, except perhaps DPSIR to certain extent. Why didnt the authors think of system dynamics models that explicitly incorporate feedbacks and are capable of integrating fast and slow dynamical systems. This also then extends to the way case studies were dealt with. Given that DPSIR approach is rather linear, I found key important aspects of feedbacks, synergies and tradeoffs between various driving, state, impact and response variables. For example, some pressures such as due to population growth might be influenced by policy responses of past actions such as providing reliable and abundant water supply. These are quite important if SDGs are to be investigated. In this regard I found the choice of the framework used by the authors as not well justified.	To reach the aim of this research to support policy development on sustainable drinking water supply, we chose to conduct three case studies to identify the main sustainability aspects in these cases. For this we decided to use DPSIR. DPSIR has previously been used for complex water systems by various well- known researchers in this field, such as Claudia Pahl-Wostl. In Binder, Hinkel et al. (2013) a comparison was made between various frameworks. The authors of that paper concluded that DPSIR was a policy framework that does not explicitly include development of a model, but aims at providing policy-relevant information, on pressures and responses on different scales. In Carr, Wingard et al. (2009) the use of DPSIR for sustainable development was evaluated. Although the authors were critical regarding the use of the DPSIR framework on national, regional or global scales, they considered application on a local scale appropriate. They concluded that practitioners can use DPSIR for local-scale studies because it assesses the place-specific nuances of multiple concerned stakeholders more realistically. In Van Noordwijk, Speelman et al. (2020) DPSIR was used to understand the joint multi-scale phenomena in the forest- water-people nexus and thus diagnosed issues to be addressed in serious games for local decision-making.	This has been elaborated in the (new) section 2.1 on the case analysis method. Line 198-239.
		In the discussion we reflected on the limitations of the linear DPSIR approach with regard to the trade-offs and feedbacks in the drinking water supply. While the aim of the research was to identify sustainability characteristics for drinking water supply on a local scale to support policy development and stakeholder involvement rather than analysis and modeling of the system dynamics, we decided to use this framework. A next step could potentially be to use the identified system characteristics for a system dynamics analysis and modeling. However, this is beyond the scope of this current research.	In the new discussion section 4.1 this has been elaborated further (line 518 -540).
3	I also had difficulties appreciating the discussion as I found tables synthesizing aspects of the three case studies repetitive. If the authors are intending to revise and resubmit, I would challenge the authors on providing a more sound basis for the choice of DPSIR framework in their pursuit of holistically assessing the sustainability of drinking water supply systems while not ignoring key aspects of feedbacks between	The tables of the case studies indeed show repetitive issues. This has been solved by removing the summarizing tables 1-3 and referring to the adjusted Appendices A-C. Concerning the remark on the dynamics in the sociohydrological, as well as the sociotechnical dynamics, we refer to the aim of the research, which was to identify the most relevant challenges that must be addressed in policy development on sustainable drinking water supply, rather than the system dynamics. In our discussion we addressed the fact that the feedbacks and trade-offs in the drinking	Appendices A-C (adjusted/new) See above. Section 4.1 (line 518-540) has

#	Referee #1 Comments (Received and published: 21 April 2020)	Authors Comments	Adjustments in new manuscript
	slow and fast dynamics of sociohydrological systems that supply systems are embedded in.	water supply cases complicated the DPSIR analysis. However, for the aim of the research, the DPSIR approach sufficed. Use of a different integrated systems approach would not have led to a significantly different outcome of the research.	been adjusted (discussion on use of DPSIR).
4	What could have been innovative would perhaps be a narrative treatment of how water supply systems might themselves have emerged from the underlying sociohydrological dynamics, locking them into a path towards unsustainable development (e.g. water supply systems that emerged in water abundant/flood prone countries might not be as resilient to drought events as those that emerged in latter drought prone systems). The case studies presented provide abundant material to shift the narrative in this direction.	Evaluation of how water supply systems developed as a result of underlying sociohydrological dynamics would indeed be a very interesting research topic. The case studies could definitely be used for this, when combined with case studies in semi-arid/arid countries. However, this is beyond the scope of the current study, which was to find sustainability characteristics.	No adjustment in manuscript.

#	Referee #2 Comments (Received and published: 24 July 2020)	Author's comments	Adjustments in new manuscript
	Sustainability characteristics of water supply were determined based on the analysis of three case studies in the Netherlands. From there general sustainability criteria were identified that can be used in to assess drinking water supply. The paper tackles an interesting subject and is well written. However, it needs some adjustment before publication.	Thank you for your kind words.	
	General comments:		
5	- The title should include the fact that the study was based on three case studies in the Netherlands.	Thank you for this suggestion. The title has been adjusted accordingly (adding "in The Netherlands").	Title has been adjusted.
6	- The paper is rather long; the writing could be more concised and redundancies should be eliminated.	We have removed several figures, integrated some of the tables and removed redundancies following your suggestions.	Fig 1-2, Table 1- 3 have been removed.
7	- When general statements are done, they should be supported by literature.	Where available references have been added. If not available, the statement has been removed.	e.g. 220-229 (Binder, Carr, Van Noordwijk)
8	- The methodology chapter is rather general, without a good description how sustainability characteristics and criteria were precisely determined.	The adopted research approach consisted of four steps. The first step was the selection and analysis of three drinking water practice cases in the Netherlands, aiming to identify the Dutch sustainability aspects in these cases. Three Dutch cases were selected based on their impact to the sustainability of drinking water supply in the Netherlands, illustrated with Vitens data (Van Engelenburg, Fleuren et al. 2020). In the second step the cases were analysed using the DPSIR framework (see section 2.1).	The method is more precisely described and clarified in section 2. Line 148-191.

		The sustainability aspects of these cases were identified in the descriptive results of the DPSIR analysis. The results were combined with Dutch governmental reports on these events and developments (Vitens 2016, Ministry of Infrastructure and Environment and Ministry of Economic Affairs and Climate Policy 2019) and cross-checked with Vitens staff. The sustainability aspects were categorized into hydrological, technical and socio-economic aspects. This resulted in a set of relevant sustainability aspects. The following step was used to broaden the perspective from the drinking water supply in the Netherlands to a more general perspective, by cross-checking the set of sustainability aspects with the targets and indicators in Sustainable Development Goal 6 (UN 2015) and the WHO Guidelines for Drinking-Water Quality (WHO 2017). Based on the analysis nine hydrological, technical and socio-economic sustainability characteristics were proposed that cover the identified sustainability aspects. In the final step of the study each sustainability characteristic was elaborated further into five sustainability criteria that describe the local drinking water supply system. This resulted in a proposal for sustainability characteristics and criteria of local drinking water supply systems that could potentially be applied in various contexts.	
9	- In addition, the sustainability criteria should be better formulated in order to be able to judge compliance (or not).	We have provided an additional appendix E to the current paper that formulates and elaborates the sustainability criteria in the following information for each of the criteria: general explanation of the criterion, description of what may be considered sustainable, under pressure and unsustainable, and suggestions for indicators or other date sources.	Additional detailed information has been provided in Appendix E.
10	- When looking at the general use of the criteria for judgement of water supply systems in the world, at least some criteria are missing, such as Non-revenue water/leakage (which is maybe not a question in the Netherlands, but internationally it is) for technical system; and cost-recovery, a good-billing system, transparency in water tariffs, equality in water billing, etc. for governance. These flaws may be avoided by better (and more systematically) addressing previous bullets.	The mentioned criteria that the second referee found missing, are implicitly accounted for in the sustainability criteria. Non-revenue water/leakage in "Technical state distribution infrastructure", cost-recovery/billing system/tariffs are implicitly accounted for in the governance criteria "Availability of (drinking) water legislation and policies" and "Compliance of drinking water supplier". We have clarified this in the elaboration of the sustainability criteria in the appendix as mentioned above.	Additional detailed information has been provided in Appendix E.
11	- Description of cases should be part of methodology section.	The case description has been moved to the method section (section 2.2), and section 3 has been limited to the results of the analysis.	Section 2.2 and section 3 have been adjusted accordingly.
12	- Avoid repetition of results in the various tables. It is better to summarize at once and then describe in the various sections.	we integrated Table 1-3 into Appendix A-C. In addition, we have moved Table 7 towards Appendix E and elaborated this into a further description of the criteria.	App. A-C, App. E have been adjusted accordingly.

13	- Discussion (with literature) should be part of "results" section and not of "conclusions" and conclusions should be concised.	ature)We have adjusted the final section, separating the discussion from the final conclusion of the paper in two separate sections, with specific attention to the conciseness of the writing.	
14	 Language, including tenses, should be checked: present tense for general statements and past tense for own findings and work. 	This has been checked and adjusted where applicable in the revised manuscript.	E.g. line 34, 37, 114, 120, 200, 261
15	 Avoid word "issues", but better "characteristics" "criteria" "aspects", depending on own definition. 	We have replaced the word 'sustainability issue' by 'sustainability aspect'. These aspects result from the DPSIR analysis and the cross- check with international policy documents (UN, WHO). The identified aspects are categorized into nine sustainability characteristics, each consequently elaborated into five sustainability criteria.	This has been adjusted where relevant throughout the manuscript.
	Specific comments:	Thank you for your detailed comments.	
16	- Line 40-44: delete (see general comments).	Has been deleted in abstract	See abstract.
17 - Line 48: delete and give H summary of results. T h s q o a e d		Has been adjusted into: This resulted in the following set of hydrological, technical and socio-economic sustainability characteristics: (1) water quality, water resource availability, and impact of drinking water abstraction; (2) reliability and resilience of the technical system, and energy use and environmental impact; (3) drinking water availability, water governance, and land and water use.	See abstract. Line 46-50.
18	- Line 56-57: too general, delete.	Has been deleted	Section 1. Line 62-63.
19	- Line 57-60: give reference.	e reference. Reference: WHO, & UNICEF. (2017). Progress on drinking water, sanitation and hygiene, 2017 update and SDG Baselines.	
20	- Line 64-67: could be shortened (little information), only references sufficient.	Has been adjusted to: For instance, two recent examples of water crises were reported in Cape Town, South Africa and São Paolo, Brazil (Sorensen, 2017, Cohen, 2016).	Section 1. Line 69-70.
21	- Line 70-71: delete sentence.	Has been deleted.	Section 1. Line 70-73.
22	- Line 84: delete sentence.	Has been deleted.	Section 1. Line 77-78.
23	 Line 90-96: not much extra information (too general without references), so consider deleting. Has been deleted. 		Section 1. Line 100-104.
24	24 - Line 102-104: delete sentence. Has been deleted.		Section 2. Line 110-111.
25	- Line 127-130: not relevant information.	Has been deleted.	Section 2 has been rewritten.
26	- Line 131: internal colleagues = staff.	Has been adjusted.	Section 2. Line 173.
27	- Line 135: how the authors came to the defined "sustainability characteristics"?	The cases were analysed using the DPSIR framework. The sustainability aspects of these cases were identified in the descriptive results of the DPSIR analysis. The results were combined with Dutch governmental reports on these events and developments and cross- checked with Vitens staff. The sustainability aspects were categorized into hydrological, technical and socio-economic aspects. This resulted in a set of relevant sustainability aspects (in the original manuscript in Tables	This is elaborated in section 2 and 2.1.

20		1-3 and App A). The following step was used to broaden the perspective from the drinking water supply in the Netherlands to a more general perspective, by cross-checking the set of sustainability aspects with the targets and indicators in Sustainable Development Goal 6 (further referred to as "SDG 6", see App. D) (UN 2015), and the WHO Guidelines for Drinking-Water Quality (WHO 2017). Based on the analysis nine hydrological, technical and socio-economic sustainability characteristics were proposed that cover the identified sustainability aspects.	
28	- Line 142: can be = could potentially be.	Original sentence has been removed.	been rewritten.
29	- Line 144: Figure 1 does not give much extra information in relation to text so can be deleted.	We have made the Methods section more concise. Because it gives the same information as the figure, we have removed this figure.	Figure has been removed.
30	- Line 147 and onwards: Section 2.1 is too general with a few references. Could be shortened to in or two sentences as introduction.	We have shortened and integrated section 2.1 of the original manuscript into the introduction of section 2.	Section 2 has been rewritten.
31	- Line 178 and onwards: could be more concised too, by at least deleting 178-182.	Sentences have been deleted or adjusted	Section 2 has been rewritten.
32	- Line 210: Figure gives little extra information, so could be deleted. By the way, when it is not an own figure, a reference should be given.	We agree that the figure does not provide significant information additional to the Methods section, therefore we have removed the figure.	Figure has been removed.
33	- Line 214: case selection should be more to the point.	We have adjusted the section on the case selection to: 'In this research three drinking water supply cases in the Netherlands have been selected. The case studies were analysed to find sustainability aspects caused by the identified pressures and short- and/or long- term responses in each case, because short- term shocks have different impacts and call for other responses than long-term stresses (Smith and Stirling 2010). The cases therefore focus on short-term events as well as long- term developments. All three cases also relate to targets set in SDG 6 (UN, 2015). The DPSIR analysis of the case studies is presented in Appendices A-C.' Additionally, we will add the	Section 2.2. Line 259-274.
		case descriptions to this section.	Line 275 and further.
34	- Line 215-219: general information without references, could be deleted.	Has been deleted	Section 2.1 has been rewritten.
35	- Line 233-240: avoid redundant information (already explained elsewhere).	Has been deleted	Section 2.1 has been rewritten.
36	- Line 246 and onwards: use Italic for the DPSIR elements.	Has been adjusted	Section 2. Line 161 and further.
37	 Line 246 and onwards: give references for the information that is given on the cases (e.g. line 247, 257, 259, 260-263,) Line 260-263: how this information is obtained/verified? 	The description of the cases is partially based on raw, unpublished operating data from Vitens, that are presented in Illustrations 1, 2 and 3. The 2018 drought was evaluated by the Ministry of Infrastructure and Environment, which report was the main source of information. A reference to the unpublished Vitens data (Van Engelenburg e.a., 2020) has been added.	Section 2.2, added to headings Figure 1-3.
38	 Line 274 and onwards: Is there a "case" or is it a "general" 	The second case is focused on how the groundwater quality development affects the	Section 2.2. Line 230 e.v.

	description. Now that is not clear. Better, focus on the "Vitens case".	tens case". groundwater abstraction for drinking water supply in the Netherlands. The illustration is an example from Vitens practice, based on	
39	- Line 343-352: redundant information, so delete.	The redundant information has been removed, we have rewritten and adjusted the full Methods section (2/2.1/2.2).	Section 2 has been rewritten.
40	- Line 360: introduce JPM.	This referred to the WHO Guidelines for drinking water quality and/or the WHO/UNICEF Joint Monitoring Programme for Water Supply, Sanitation and Hygiene. This has been adjusted into WHO Guidelines instead of using the abbreviation.	Explained in section 2. Line 182.
41	 Line 367: check table 4, e.g. what is difference between "raw water" and "surface water" or "groundwater"; "impact of abstraction" is redundant; "water quantity" = "water flows". See also general comments. Raw water = the water that is used for the drinking water production. This can be abstracted groundwater or surface water, depending on the used water resource. Water resources availability refers to the availability of the water resources for drinking water production based on characteristics of the hydrological system, whereas the impact of the abstraction to the hydrological system, and depends on the size and nature of the 		Footnote 1 on raw water. Line 335.(Appendix E).
42	- Line 378-383: too speculative. Please stick to own findings (and discuss in relation to literature).	Has been adjusted	Section 3.1. Line 408-410.
43	 Line 390: this will also impact costs of investments and thus water tariff. 	Has been mentioned in section 3.3	Section 3.3. Line 503-504.
44	- Line 396: delete sentence.	Has been deleted	Section 3.3. Line 426-427
45	- Line 444 and 469: why is the existence of a WSP a sustainability criterium?	Drinking water safety is a prerequisite for public health and sustainable drinking water supply. The WHO Guidelines consider water safety plans as essential to provide the basis for system protection and process control to ensure water quality issues present a negligible risk to public health and that water is acceptable to consumers. A WSP can be built on various safety protocols. We have added this to the manuscript, and we adjusted the name of the criterion into 'water safety protocols'.	Section 3.3. Line 478-485.
46	- Line 476 and onwards: avoid repetitions with previous sections, see earlier comments.	Table 7 has been adjusted in App E with an elaboration of the sustainability criteria.	Table has been removed. Appendix E has been added.
47	- Line 490-501: delete (see general comments).	We have adjusted this as a part of the discussion.	Section 4.2
48	- Line 503-510: delete (see general comments).	Has been deleted.	Line 541-551.
49	- Line 521-529: delete (see general comments).	Has been deleted.	Line 561-568.

- References

- Binder, C. R., J. Hinkel, P. W. G. Bots and C. Pahl-Wostl (2013). "Comparison of frameworks for analyzing social-ecological systems." <u>Ecology and Society</u> **18**(4): 26-45.
- Carr, E. R., P. M. Wingard, S. C. Yorty, M. C. Thompson, N. K. Jensen and J. Roberson (2009).
 "Applying DPSIR to sustainable development." <u>INT J SUST DEV WORLD</u> **14**(6): 543-555.

- Ministry of Infrastructure and Environment and Ministry of Economic Affairs and Climate Policy (2019).
 Nederland beter weerbaar tegen droogte; Eindrapportage Beleidstafel Droogte (The Netherlands more resilient to drought; final report policy table drought). The Hague, the Netherlands: 77.
- Smith, A. and A. Stirling (2010). "The Politics of Social-ecological Resilience and Sustainable Sociotechnical Transitions." <u>ECOL SOC</u> **15**(1): 11.
- UN (2015). Transforming our world: The 2030 Agenda for Sustainable Development, United Nations. A/RES/70/1: 21.
- UN (2018). Sustainable Development Goal 6 Synthesis Report 2018 on Water and Sanitation. U. Water. New York, USA, United Nations: 199.
- UNICEF and WHO (2015). Progress on Sanitation and Drinking Water; 2015 Update and MDG Assessment, UNICEF and World Health Organization: 90.
- Van Engelenburg, J., M. Fleuren and M. De Jonge (2020). Drinking water production data 2018-2020 and groundwater quality data 1985-2020 (unpublished). Vitens, Vitens.
- Van Noordwijk, M., E. Speelman, G. J. Hofstede, A. Farida, A. Y. Abdurrahim, A. Miccolis, A. L. Hakim, C. N. Wamucii, E. Lagneaux, F. Andreotti, G. Kimbowa, G. G. C. Assogba, L. Best, L. Tanika, M. Githinji, P. Rosero, R. R. Sari, U. Satnarain, S. Adiwibowo, A. Ligtenberg, C. Muthuri, M. Peña-Claros, E. Purwanto, P. Van Oel, D. Rozendaal, D. Suprayogo and A. J. Teuling (2020). "Sustainable Agroforestry Landscape Management: Changing the Game." Land **9**(8).
- Vitens (2016). Resiliently ahead; Long-term vision on our infrastructure 2016-2040. Zwolle, The Netherlands, Vitens: 36.
- WHO (2017). Guidelines for drinking-water quality: fourth edition incorporating the first addendum. Geneva, World Health Organization: 631.
- WHO and UNICEF (2017). Progress on drinking water, sanitation and hygiene, 2017 update and SDG Baselines. Geneva, World Health Organization (WHO) and UNICEF: 116.

Sustainability characteristics of drinking water supply in the Netherlands

3 Jolijn van Engelenburg¹, Erik van Slobbe², Adriaan J. Teuling³, Remko Uijlenhoet³, 4,

- 4 Petra Hellegers⁵⁴
- ⁵ ¹ Asset Management Department, Vitens NV, P.O.Box 1205, 8001 BE Zwolle, Netherlands
- ⁶ ² Water Systems and Global Change Group, Wageningen University & Research, P.O. Box
- 7 47, 6700 AA Wageningen, Netherlands
- 8 ³ Hydrology and Quantitative Water Management Group, Wageningen University &
- 9 Research, P.O. Box 47, 6700 AA Wageningen, Netherlands
- 10 <u>⁴ Water Management Department, Civil Engineering and Geosciences Faculty, Delft</u>
- 11 University of Technology P.O. Box 5048, 2600 GA Delft, Netherlands
- 12 ⁵ Water Resources Management Group, Wageningen University & Research, P.O. Box 47,
- 13 6700 AA Wageningen, Netherlands
- 14

15 Corresponding author:

- 16 Jolijn van Engelenburg
- 17 Vitens NV
- 18 P.O. Box 1205, 8001 BE Zwolle
- 19 Netherlands
- 20 Telephone: +31651525936
- 21 E-mail: jolijn.vanengelenburg@wur.nl; jolijn.vanengelenburg@vitens.nl;
- 22 jvanengelenburg247@gmail.com
- 23

24 Biography corresponding author

- 25 PhD-candidate at Wageningen University & Research and Asset manager at Drinking water
- 26 company Vitens, the Netherlands
- 27
- 28 Keywords
- 29 Systems approach; DPSIR; drinking water supply; local scale; sustainability

30

31 Abstract

Developments such as climate change and growing demand for drinking water threaten the 32 sustainability of drinking water supply worldwide. To deal with this threat, adaptation of 33 drinking water supply systems is imperative, not only on a global and national scale, but 34 particularly on a local scale. This investigation sought to establish characteristics that describe 35 the sustainability of local drinking water supply. The hypothesis of this research was that 36 sustainability characteristics depend on the context that is analysed and therefore a variety of 37 cases must be analysed to reach a better understanding of the sustainability of drinking water 38 supply in the Netherlands. Therefore t⁺hree divergent cases on drinking water supply in the 39 Netherlands weare analysed. One case relateds to a short-term development, (the 2018) 40 summer drought), and two concerned long-term phenomena, that is, (changes in water 41 quality and growth in drinking water demand). We used an integrated systems approach, 42 describing the local drinking water supply system in terms of hydrological, technical and socio-43 economic characteristics that determine the sustainability of a local drinking water supply 44 system. The approach taken recognises that next to extreme weather events, socio economic 45 developments will be among the main drivers of changes in drinking water supply. Effects of 46 pressures associated with, for example, population growth, industrial developments and land 47 48 use changes, could result in limited water resource availability, deteriorated groundwater quality and growing water demand. To gain a perspective on the case study findings broader 49 than the Dutch context, the sustainability issueaspects identified were paired with global 50 issueaspects concerning sustainable drinking water supply. This resulted in the following set 51 of hydrological, technical and socio-economic sustainability characteristics, respectively: (1) 52 53 water quality, water resource availability, and impact of drinking water abstraction; (2) 54 reliability and resilience of the technical system, and energy use and environmental impact; (3) drinking water availability, water governance, and land and water use. This resulted in a 55 proposed set of generally applicable sustainability characteristics, each divided into five 56 criteria describing the hydrological, technical and socio-economic sustainability of a local 57 drinking water supply system. Elaboration of these sustainability characteristics and criteria 58 into a sustainability assessment can provide information on the challenges and trade-offs 59 inherent in the sustainable development and management of a local drinking water supply 60 system. 61

62

63 **1 Introduction**

Climate change combined with a growing drinking water demand threatens the sustainability 64 of the drinking water supply worldwide. The goal set for drinking water supply in Sustainable 65 Development Goal (SDG) 6.1 (UN, 2015) is "to achieve universal and equitable access to safe 66 and affordable drinking water for all by 2030". Reaching this goal is complicated by changing 67 climate variability combined with socio-economic problems and developments. Worldwide 68 69 drinking water supply crises are visible, resulting from a combination of limited water resource availability, lacking or failing drinking water infrastructure and/or increased drinking water 70 demand, due to short-term events or long-term developments (WHO, 2017b). Still, nearly 10 71 percent of the world population is fully deprived of improved drinking water resources (Ekins 72 et al., 2019), and, additionally, existing drinking water supply systems often are under 73 74 pressure. For instance, two recent examples of water crises were reported in Cape Town, 75 South Africa and São Paolo, Brazsil_(Sorensen, 2017, Cohen, 2016). (- In Cape Town, found that at the end of each summer water use is restricted, pending the winter rains to set in. In 76 São Paolo, drinking water supplies are at a historic low, and on a daily base water pressures 77

are lowered to reduce the water use, which especially affects the poor. To deal with such
challenges and threats to safe and affordable drinking water, adaptation of the current
drinking water supply system is imperative, not only on a global and national level, but also
on a local scale.

Typically, the spatial or temporal scale determines whether drinking water supply is 82 considered sustainable, given the set goals. In the Netherlands, for instance, the national 83 drinking water supply currently meets the indicator from SDG 6 (UN, 2018) on safely managed 84 drinking water services and safely treated waste water. At the same time the more specific 85 goals on (local) water quantity, quality, and ecology as set by the European Water Framework 86 Directive (WFD), are not met yet (European Environment Agency, 2018). Consequently, there 87 still are sustainability issueaspects for drinking water supply in the Netherlands does not meet 88 all SDG 6 indicators, for instance when considering due to water shortage (Ministry of 89 Infrastructure and Environment and Ministry of Economic Affairs and Climate Policy, 2019), 90 impact to water-related ecosystems (Van Engelenburg et al., 2017), or water pollution (Kools 91 et al., 2019, Van den Brink and Wuijts, 2016), or -water shortage (Ministry of Infrastructure 92 and Environment and Ministry of Economic Affairs and Climate Policy, 2019). Additionally, 93 future developments such as the uncertain drinking water demand growth rate (Van der Aa 94 et al., 2015) and the changing climate variability (Teuling, 2018), may put the sustainability of 95 the Dutch drinking water supply under pressure in the future. 96

97 The interaction with its local environment affects the sustainability of local drinking water 98 supply. The abstraction of groundwater or surface water from the hydrological system, and 99 subsequent treatment to drinking water quality before being distributed to customers, 100 requires a local infrastructure (typically a drinking water production facility, embedded in a

12

101 distribution network of pipelines). Although the daily routine of drinking water supply has a highly technical character (Bauer and Herder, 2009), the sustainability in the long-term 102 depends on the balance between technical, socio-economic and environmental factors. This 103 balance is especially complex for local drinking water supply, which is intertwined with the 104 105 local hydrological system and local stakeholders through its geographical location. -- Local hydrology for instance determines the physical vulnerability to pollution from e.g. land use, 106 and to reduced water resource availability during drought. It also determines the impact of 107 the abstraction to groundwater levels, and to land use and local stakeholders, and thus affects 108 the sustainability of local drinking water supply. 109

Because of the interconnections between physical, technical, and socio-economic factors as 110 well as across space, organizational levels and time, adaptation of the local drinking water 111 supply to current and future sustainability challenges calls for an integrated planning approach 112 (Liu et al., 2015). Integrated models have been developed to understand the complex 113 interactions between the physical, technical and socio-economic components in various water 114 115 systems (Loucks et al., 2017). Systems integration, considering all system characteristics, will 116 help to identify the sustainability challenges in a system (Liu et al., 2015). However, a systems analysis to assess local drinking water supply and to identify sustainability challenges on a local 117 scale has not yet been developed. 118

This research aim<u>eds</u> to propose a set of sustainability characteristics that describe the drinking water supply system on a local scale to support policy- and decision-making on <u>sustainable drinking water supply</u>. To reach this aim, cases on drinking water supply <u>awe</u>re analysed using a conceptual framework. The selected cases represent<u>ed</u> a short-term event and long-term developments that affect water quality and water resource availability, the technical drinking water supply infrastructure and/or the drinking water demand. The system
boundaries weare set to drinking water supply on the local scale. While the drinking water
supply on a local scale is also affected by outside influences from different organizational and
spatial scales, the analysis accounteds for these external influences too. The hypothesis of this
research was that sustainability characteristics depend on the context that is analysed and
therefore a variety of cases must be analysed to reach a better understanding of the
sustainability of drinking water supply in the Netherlands.

131

132 **2 Method**

Sustainable water systems can be defined as water systems that are designed and managed 133 to contribute to the current and future objectives of society, maintaining their ecological, 134 environmental, and hydrological integrity (Loucks, 2000). This study focusesd on the 135 sustainability of drinking water supply systems on a local scale, in short, local drinking water 136 supply systems. The boundaries of these systems awere set by the area in which drinking 137 water abstraction is embedded. The system can be approached from different perspectives. 138 The socio-ecological approach considers relations between the socio-economic and 139 environmental system, whereas the socio-technical approach considers the socio-economic 140 and technical system (Pant et al., 2015). In this study we combined both approaches by 141 describing the local drinking water supply system in terms of hydrological, technical and socio-142 economic characteristics that determine the sustainability of a local drinking water supply 143 system. 144

Drinking water supply in the Netherlands is of a high standard compared to many other
 countries. The SDG 6 targets on safe and affordable drinking water and sanitation and

147 wastewater treatment are basically met. But the Dutch government and drinking water 148 suppliers are also challenged to meet the other goals set in SDG 6, such as improvement of 149 water quality, increase of water-use efficiency, and protection and restoration of water-150 related ecosystems. In addition the standards on water quantity, quality, and ecology as set 151 by the European Water Framework Directive (WFD) have not been achieved yet (European 152 Environment Agency, 2018).

The adopted research approach consisteds of four steps. The first step wais the selection and 153 analysis of three drinking water practice cases in the Netherlands, aiming to identify the main 154 Dutch sustainability issueaspects in these cases. In step 2 these issues are categorised, and 155 used to propose a set of characteristics that describe the sustainability of the local drinking 156 water supply system. In step 3 the sustainability issues from the case studies are cross-checked 157 with global drinking water supply issues, which in step 4 leads to a set of sustainability criteria 158 that describe the local drinking water supply system. The research method outline is presented 159 160 in Fig. 1.

Three Dutch cases were selected based on their <u>potential to negatively affect impact to</u> the sustainability of drinking water supply in the Netherlands, considering <u>-a short-term event</u> <u>with limited water resource availability, as well as long-term ongoing developments on water</u> <u>quality, and growing drinking water demand and water resource availability. The cases are</u> <u>illustrated with Vitens data (Van Engelenburg et al., 2020b).</u>

In the second step the cases were analysed using the DPSIR framework (*Driver, Pressure, State, Impact, Response* (Eurostat, 1999), see section 2.1). The sustainability aspects of these cases
 were identified in the descriptive results of the DPSIR analysis. The results The aim was to
 identify sustainability issues in a short-term event such as extreme summer drought or other

disturbances, and the issues resulting from long term ongoing developments on water quality, 170 water resource availability, or drinking water demand. Because the first author of this article 171 is employed at a drinking water supplier (Vitens, the Netherlands), this provided the 172 researchers with in-depth knowledge of current practice in the Netherlands, obtained through 173 professional involvement in internal and external discussions and meetings on the topics of 174 175 the cases. The results of the case studies were cross checked with internal colleagues within 176 Vitens, and combined with Dutch governmental reports on these events and developments (Ministry of Infrastructure and Environment and Ministry of Economic Affairs and Climate 177 Policy, 2019, Vitens, 2016) and- cross-checked with Vitens staff. In section 3 the cases are 178 described, and illustrated with Vitens data(Van Engelenburg et al., 2020b), summarising the 179 sustainability issues resulting from the case studies. The sustainability aspects were 180 181 categorized into hydrological, technical and socio-economic aspects. This resulted in a set of 182 relevant sustainability aspects, which is- presented in Appendices A-C. re subdivided into hydrological, technical and socio-economic issues. The following step was 183 used to broaden the perspective from the drinking water supply in the Netherlands to a more 184 general perspective, by cross-checking the set of sustainability aspects with the targets and 185 indicators in Sustainable Development Goal 6 (further referred to as "SDG 6", see App. D) (UN, 186 2015), and the WHO Guidelines for Drinking-Water Quality (WHO, 2017a). The sustainability 187 aspects as identified in the analysis were categorized into nine hydrological, technical and 188 socio-economic sustainability characteristics. In the final step of the study each sustainability 189 190 characteristic was elaborated further into five sustainability criteria that describe the local drinking water supply system. The results are described in section 3. A detailed description of 191 the resulting sustainability criteria is presented in Appendix E. To cross check and broaden the 192 perspective from the drinking water supply in the Netherlands to a more general perspective, 193







201 Figure 1 Outline research method.

202 **2.1 Case analysis method**

To reach the aim of this research to support policy development on sustainable drinking water 203 204 supply, three practice cases weare analysed to identify the main sustainability aspects in these cases using the DPSIR (Driver-Pressure-State-Impact-Response) systems approach (Eurostat, 205 1999): Drivers describe future developments such as climate change and population growth. 206 Pressures are developments (in emissions or environmental resources) as a result from the 207 drivers. The state describes the system state that results from the pressures. In this research 208 209 the aim is to describe the system state of the drinking water supply system in terms of local hydrological, technical and socio-economic sustainability characteristics (see section 2.1). The 210 changes in system state cause impacts to system functions, which will lead to societal 211 responses. DPSIR was originally developed to describe causal relations between human 212 actions and the environment. It has also frequently been used for relations and interactions 213 between technical infrastructure and the socio-economic and physical domain (Pahl-Wostl, 214 215 2015, Hellegers and Leflaive, 2015, Binder et al., 2013).

The DPSIR approach was used for the analysis of the three selected drinking water supply 216 cases to obtain an overview of the impact of drivers, pressures and responses to the state of 217 218 the drinking water supply system. Although the framework has been applied on different 219 spatial scales, Carr et al. (2009) recommend using the framework place-specific, to ensure that 220 local stakeholder perspectives are assessed as well. With the research focus at the local drinking water supply system, these local perspectives weare implicitly included. The drivers, 221 pressures and responses can be on local as well as higher organizational and/or spatial scales, 222 thus ensuring that - where essential - relevant higher scales are accounted for too. 223

224 -DPSIR has previously been used for complex water systems by various well-known researchers in this field, such as Claudia Pahl-Wostl. In Binder et al. (2013) a comparison was 225 made between various frameworks, which concluded that DPSIR is a policy framework that 226 does not explicitly include development of a model, but aims at providing policy relevant 227 information, on pressures and responses on different scales. In Carr et al. (2009) the use of 228 DPSIR for sustainable development was evaluated. Although the authors were critical 229 regarding the use of the DPSIR framework on national, regional or global scales, they 230 considered application on a local scale appropriate. They concluded that practitioners can 231 use DPSIR for local-scale studies because it assesses the place-specific nuances of multiple 232 233 concerned stakeholders more realistically. In Van Noordwijk et al. (2020) DPSIR was used to understand the joint multi-scale phenomena in the forest-water-people nexus and thus 234 235 diagnosed issues to be addressed in serious games for local decision-making. Therefore, 236 DPSIR was considered an appropriate framework to meet the aim of the research. The impact of developments on different temporal scales to the drinking water supply system 237 238 must be taken into accountconsidered as well. The long lived, interdependent drinking water supply infrastructure is rigid to change due to design decisions in the past, which is causing 239 path-dependencies and lock-ins (Melese et al., 2015). In addition, consumer behaviour, 240 governance and engineering, and the interaction between these processes cause lock-in 241 situations that limit the ability to change towards more sustainable water resources 242 management (Pahl-Wostl, 2002). For this reason, the case analysis wais performed 243 considering both short- and long-term pressures, impacts and responses. (Fig. 2). 244



Figure 2 Analysis of the local drinking water supply system, using DPSIR, considering short term and long-term pressures (P), responses (R) and impact (I), to identify the sustainability
 issues affecting the state of the system.

250 2.2 Case selection

245

249

Sustainability challenges faced by drinking water supply worldwide are (1) how to respond to 251 252 short-term events such as extreme drought or other disturbances, and (2) how to adapt to long term developments that limit the water resource availability, or cause a strong drinking 253 water demand growth. The challenges for drinking water supply in the Netherlands are in 254 nature comparable to these global challenges. Drinking water supply in the Netherlands is of 255 a high standard compared to many other countries. The SDG 6 targets on safe and affordable 256 drinking water (SDG 6.1/6.2) and sanitation and waste water treatment (SDG 6.3) are basically 257 met. But the Dutch government and drinking water suppliers are also challenged to meet the 258 other goals set in SDG 6, such as improvement of water guality (SDG 6.3), increase of water-259 260 use efficiency (SDG 6.4), integrated water resources management (SDG 6.5), protection and restoration of water related ecosystems (SDG 6.6), and the more specific standards on water 261 quantity, quality, and ecology as set by the European Water Framework Directive (WFD) 262 (European Environment Agency, 2018). 263

264 For the first step of In this research three drinking water supply cases in the Netherlands have beenwere selected. The cease studies were analysed using DPSIR were performed to 265 find sustainability issueaspects caused by the identified pressures and short- and/or long-266 term responses in each case, because short-term shocks have different impacts and call for 267 other responses than long-term stresses (Smith and Stirling, 2010). The cases therefore 268 focused on short-term events as well as long-term developments., because short-term 269 shocks have different impacts and call for other responses than long term stresses (Smith 270 and Stirling, 2010). The first case "2018 Summer drought" deals with the impact of an 271 extreme drought period in the summer of 2018 in the Netherlands, not only affecting 272 drinking water demand and availability, but also limiting water resources for other uses than 273 drinking water, as well as water-related ecosystems (Ministry of Infrastructure and 274 275 Environment and Ministry of Economic Affairs and Climate Policy, 2019). Cases 2 and 3 deal 276 with long term developments in the Netherlands on groundwater quality (Kools et al., 2019) and on drinking water demand (Baggelaar and Geudens, 2017, Van der Aa et al., 2015), 277 respectively. All three cases also related to targets set in SDG 6 (UN, 2015). The complete 278 279 results of the DPSIR analysis of the case studies is are presented in Appendices. A-C.

280 Case 1 "2018 Summer drought"

Summer 2018 in the Netherlands was extremely warm and dry, causing water shortages in the water system, and a long period of extreme daily drinking water demand, resulting in a record monthly water demand in July 2018 ((Ministry of Infrastructure and Environment and Ministry of Economic Affairs and Climate Policy, 2019) (see Illustration case 1, Fig. 3). The *driver* in this case is the extreme weather condition, which caused several *pressures*, such as high temperatures, high evaporation and lack of precipitation. These *pressures* did not only cause drought damage to nature, agriculture and gardens and parks, as well as limited water 288 availability in the surface water and groundwater systems, they also resulted in an extremely high drinking water demand-(Ministry of Infrastructure and Environment and Ministry of 289 Economic Affairs and Climate Policy, 2019). Data on drinking water supply volumes (Van 290 Engelenburg et al., 2020b) showed that t⁺he extreme drinking water demand during summer 291 292 2018 put the drinking water supply system under high pressure, resulting causing extremein daily and monthly drinking water supply volumes that exceeded all previously supplied 293 volumes (see Illustration case Fig. 1). The capacity of the system was fully exploited, but faced 294 limitations in abstraction, treatment and distribution capacity. 295

Illustration case 1: 2018 Summer drought

Within the Vitens supply area the average daily supply volume during the summer period June-August over the years 2012-2017 was approximately 965,000 m³/day. During the period 27 June-4 August 2018 the daily supply volume exceeded this average summer volume with approximately 28%, with an average volume of nearly 1,240,000 m³/day (Fig. 4.31a). On 25 July 2019 the maximum daily water supply reached nearly 1,390,000 m³/day, which was 42% above the baseline daily supply (Fig. 4.3a1a). The monthly drinking water supply volume in July 2018 of 38 million m³/month was an increase of 18% compared to the previous maximum monthly supply volumes (Fig. 4.3b1b). Although the drinking water supply infrastructure was designed with an overcapacity to meet the regular demand peaks, the flexibility to more extreme peaks, or to long periods of peak demand is limited.



296

The high drinking water abstraction volumes added up to the water shortages in both the groundwater and the surface water system caused by the lack of precipitation and high evaporation during the summer_(Ministry of Infrastructure and Environment and Ministry of Economic Affairs and Climate Policy, 2019). To ensure an acceptable surface water quality for the drinking water supply, measures were taken to reduce salinization_(Ministry of Infrastructure and Environment and Ministry of Economic Affairs and Climate Policy, 2019).

To reduce the drinking water use, a call for drinking water saving was made, and locally 303 pressures in the drinking water distribution system were intentionally lowered to reduce the 304 305 delivered drinking water volumes (Ministry of Infrastructure and Environment and Ministry of Economic Affairs and Climate Policy, 2019). The problems caused by the summer drought 306 307 raised a discourse on (drinking) water use and saving, including discussions on controversial measures such as a progressive drinking water tariffs, with tariffs dependent on the consumed 308 drinking water volume, and differentiation between high-grade and low-grade use of 309 310 (drinking) water (Ministry of Infrastructure and Environment and Ministry of Economic Affairs and Climate Policy, 2019). Table 1 summarizes the impacts, responses and sustainability issues 311 The results of this case analysis are presented in App. A. 312

313 Case 2 "Groundwater quality development"

This case focusesd on the impact of the groundwater quality development in the Netherlands to the drinking water supply. In the Netherlands 55% of the drinking water supply is provided by groundwater resources (Baggelaar and Geudens, 2017)=Analysis of the state of the drinking water resources for drinking water supply in the Netherlands in 2014 pointeds out that, although the drinking water quality meets met the Dutch legal standards, all water resources are under threat by known and new pollutants (Kools et al., 2019). In the Netherlands 55%

320 of the drinking water supply is provided by groundwater resources (Baggelaar and Geudens, 2017). Long-term analysis of water quality records of Dutch drinking water supply fields shows 321 that the vulnerability of groundwater resources to external influences such as land use 322 323 strongly depends on hydrochemical characteristics (Mendizabal et al., 2012). Monitoring results show that currently groundwater quality is mainly under pressure due to nitrate, 324 pesticides, historical contamination and salinization (Kools et al., 2019). Nearly half of the 325 groundwater abstractions for drinking water are affected by an insufficient groundwater 326 <u>quality</u>, and it is expected that in the future the groundwater quality at more abstractions will 327 exceed the groundwater standards set in the European Water Framework Directive (European 328 Union, 2000). In addition, traces of pollutants such as recent industrial contaminants, 329 medicine residues and other emerging substances are found, indicating that the groundwater 330 331 quality will likely further deteriorate (Kools et al., 2019).

Groundwater protection regulations regarding land and water use by legal authorities will 332 333 help to slow down groundwater deterioration (Van den Brink and Wuijts, 2016). However, strategies to restore groundwater quality often will not be effective in the short term, 334 because already existing contaminations may remain present for a long period of time, 335 depending on the local hydrological characteristics (Jørgensen and Stockmarr, 2009) (see 336 Illustration case 2). The impact of contamination cannot be undone, unless soil processes 337 help to (partially) break down contaminants. Thorough monitoring for pollution therefore is 338 essential to follow groundwater quality trends and to respond adequately to these trends 339 340 (Janža, 2015). Due to the expected deterioration of the raw water quality¹, different and 341 more complex treatment methods are necessary to continuously meet the drinking water

¹ Raw water is the (untreated) water that is treated used- to produce for the drinking water-production. This can be abstracted groundwater or surface water depending on the used available water resource.

standards (Kools et al., 2019). In general, a more complex treatment method leads to higher
 energy use, use of additional excipients, water loss and production of waste materials, which
 will lead to a higher water tariff, and to a higher environmental impact (Napoli and Garcia-

Tellez, 2016). The results of the analysis are presented in App. B. Table 2 summarises the

346 impacts, responses and sustainability issues of this case.

Illustration case 2: Groundwater quality development

In the 1980's the Dutch government installed regulations to protect water quality by limiting the growing nitrate and phosphate surplus due to overuse of livestock manure. This resulted in a decrease of the nitrate surplus from 1985 on. However, due to the long travel times in groundwater it took years before the impact of these regulations became visible in the groundwater quality. Fig. 4.42 illustrates the period of time in which the nitrate concentration in an abstraction well still increased despite the 1985 regulations on reduction of the nitrate surplus at surface level: the nitrate concentration in this well has increased until 2005 before the nitrate level started to decrease. Only since 2014 the concentration has dropped below the nitrate standard for groundwater of 50 mg/L.



Figure 42 Development of nitrate in an abstraction well in Montferland (HEE-P07-07.0, coordinates X213.540-Y434.761) in the province of Gelderland, the Netherlands (Van Engelenburg et al., 2020b) (data source Vitens) compared to the Dutch standard for nitrate concentration in groundwater (50 mg/L).

348 Case 3 "Drinking water demand growth"

Due to drinking water saving strategies the drinking water use in the Netherlands per person 349 has decreased from 137 litre per person per day in 1992 to 119 litre per person per day in 350 2016 (Van Thiel, 2017). This development resulted in a decreasing total yearly drinking water 351 352 demand volume in that same period, despite the population growth in the Netherlands (Baggelaar and Geudens, 2017). However, 2013 was a turning point, when the total yearly 353 drinking water demand volume in the Netherlands started to grow again (Baggelaar and 354 Geudens, 2017). The trend in the period 2013-2019 shows a strong increase in drinking water 355 demand (see Illustration case 3). Delta scenarios have been developed for the Netherlands, 356 projecting a drinking water demand development varying between a decrease of 10% to an 357 358 increase of 35% in 2050 compared to 2015 (Wolters et al., 2018).

The drinking water demand growth rate of the period 2013-2019 as is seen within the Vitens supply area compares to the growth rate in the maximum delta scenario of 35% growth from 2015 to 2050 (See Illustration case 3).

Illustration case 3: Drinking water demand growth

The increase in normalised drinking water supply volume as supplied by Vitens between 2015 and 2019 is 4.5% (Fig. 4.53). Due to this recent demand growth the reserve capacity within the existing drinking water supply infrastructure is already limited. The drinking water demand growth rate of the period 2015-2019 compares to the growth rate in the maximum delta scenario of 35% growth from 2015 to 2050 (Fig. 4.53). If this growth rate is not tempered through a significant reduction of the drinking water use, this would require a large extension of the drinking water supply infrastructure.



Figure 53 Development of the normalised annual drinking water volume supplied by Vitens (drinking water supplier), the Netherlands 2003-2019_(Van Engelenburg et al., 2020b), compared to the projected Delta scenarios on drinking water demand growth (Wolters et al., 2018), ranging between a decrease of 10% to an increase of 35% in 2050 compared to 2015. The normalized annual drinking water supply volume excludes the impact of extreme weather conditions on the actual supplied annual volumes of drinking water.

362

363

If this strong growth rate continues, this will put serious pressure on the drinking water supply.
This will partially be due to limitations in the technical infrastructure, but also partially due to
limitations in the water resource availability, caused by insufficient abstraction permits, or a
possibly negative impact to the hydrological system and stakeholders. Given the inflexibility
of drinking water supply infrastructure to change, an integrated strategy is necessary to meet

369 this uncertain development of the drinking water demand. To find sustainable solutions for 370 the future not only the technical infrastructure issue<u>aspect</u>s must be solved. It also requires strategies on water saving, expansion of permits, development of new abstraction concepts 371 using other water resources, as well as stakeholder processes in the design and use of the 372 local drinking water supply system. This case is basically an extension to the first two cases: 373 374 the growing water demand amplifies the issueaspects caused by the drought in 2018 and the groundwater quality development. Table 3 therefore only summarises the additional 375 sustainability issues with respect to the first two cases. The results of the analysis of this case 376 study are presented in App. C. 377

378 3 Sustainability characteristics of drinking water supply

The first research step (see Fig. 1) resulted in a summary of the sustainability issues for the 379 local drinking water supply system found in the selected cases. In this section the results from 380 research step 1 are combined with the results from research steps 2 to 4 (see Fig. 1). In step 2 381 382 the sustainability issues from the case studies are categorised into nine hydrological, technical and socio-economic sustainability characteristics. In research step 3, these issues were cross-383 checked with the targets and indicators in Sustainable Development Goal 6 (further referred 384 to as "SDG 6", see App. B) (UN, 2015) and the 2017 update of the WHO/UNICEF Joint 385 Monitoring Programme for Water Supply, Sanitation and Hygiene (further referred to as 386 387 "JMP") (WHO and UNICEF, 2017). In the final step of the study each sustainability characteristics are presented, each is elaborated further into five sustainability criteria. A 388 detailed description of the resulting sustainability criteria can be found in Appendix E. 389

390 **3.1 Hydrological sustainability characteristics**

Three hydrological sustainability characteristics <u>a</u>-re proposed that summarise the hydrological <u>issueaspect</u>s affecting the drinking water supply as found in the case studies: *water quality, water resource availability* and *impact of drinking water abstraction* (Table 1).-

394 Table 4 provides a summary of the results of the subsequent research steps (see Fig. 1).

395	Water quality includes the monitoring and evaluation of current water quality, and the trends
396	and expected future development of the water quality and emerging contaminants, as
397	described in the case "Groundwater quality development". In the WHO Guidelines for
398	Drinking-Water Quality (WHO, 2017a) JMP additionally the importance of microbial aspects
399	as a global water quality issueaspect with a health impact is monitored, such as bacteriological
400	contamination due to untreated waste water or emergencies(WHO and UNICEF, 2017)The
401	WHO Guidelines for Drinking-Water Quality (WHO, 2017a)_JMP also requires monitoring of
402	monitors-water quality aspects without health impact, such as salinization, water hardness,
403	and colour, which affect the acceptability of the drinking water (WHO and UNICEF, 2017).

404	Table-4<u>1</u> Summary of proposed hydrological sustainability characteristics, hydrological <i>issueaspects</i>
405	from case studies (see Tables 1-3 <u>App. A-C</u>), relevant SDG ¹ indicators and <u>WHO Guidelines for</u>
406	<u>Drinking-Water Quality (</u> WHO, 2017a) <u>JMP² issueaspect</u> s, and hydrological sustainability criteria.

Hydrological sustainability characteristics	Water quality	Water resource availability	Impact of drinking water abstraction
Sustainability issueaspects from case studies	Monitoring and evaluation Sources of pollution Contaminants Emerging contaminants Groundwater quality Surface water quality Raw water quality	Other water resources Surface water quantity Groundwater quantity Vulnerability of the water system Drought impact Water discharge	Impact of abstraction Groundwater levels Abstraction volume Balance between annual recharge and annual abstraction Hydrological compensation
SDG 6 targets ¹	6.3, 6.5	6.4, 6.5	6.4, 6.6
WHO Guidelines for Drinking- Water Quality	Health risks from microbial contamination	Small- or large-scale emergencies caused by natural hazards, such as droughts, floods, earth	-

Hydrological sustainability characteristics	Water quality	Water resource availability	Impact of drinking water abstraction
(WHO, 2017a) JMP²	Acceptability of the drinking water (salinization, hardness, colour)	quakes<u>earthquakes</u> or forest fire	
Sustainability	Current raw water quality	Surface water quantity	Impact on surface water
criteria	Chemical aspects of water	Groundwater quantity	system
	quality	Other available water	Impact on groundwater system
	Microbial aspects of water	resources	Balance between annual
	quality	Vulnerability <u>used</u> water	recharge and abstraction
	Acceptability aspects of	system water for	Hydrological compensation
	water quality	contamination	Spatial impact of abstraction
	Monitoring and evaluation of water quality trends	Natural hazards and emergencies risk	facility/ storage/reservoir

¹ SDG = Sustainable Development Goal; see App. V for summary of Sustainable Development Goal 6 targets and
 indicators related to sustainability characteristics (UN, 2015)

Water resource availability for drinking water supply can be differentiated into the surface 409 410 water and groundwater availability, as illustrated in Case 1 "2018 Summer drought". Other 411 sustainability issueaspects are the vulnerability of the surface and/or groundwater system to the water quality being affected permanently by land use, as illustrated in the case 412 "Groundwater quality development". These issues are also relevant when considering a shift 413 to other resources, for instance from groundwater resources to surface water resources for 414 drinking water supply. The water resource availability can also be limited due to small- or 415 416 large-scale emergencies caused by natural hazards, such as droughts, floods, earth-quakes or 417 forest fires (WHO and UNICEF, 2017), that will put the sustainability of the local drinking water supply under pressure. 418

The *impact of the drinking water abstraction* to the hydrological system entails the impact to both the surface water system and the groundwater system, but also the balance between the annual drinking water abstraction volume and the annual recharge of the (local) water system. Whether the impact of the abstraction is or can possibly by compensated hydrologically is another sustainability <u>issueaspect</u>. The spatial impact of the local drinking water abstraction facility may also be a sustainability <u>issueaspect</u>: a drinking water facility requires a certain water storage area or reservoir, which might have a significant spatial
impact in the area and thus might affect local stakeholders.

427 **3.2 Technical sustainability characteristics**

Three technical sustainability characteristics are proposed that summarise the technical issueaspects for the drinking water supply as found in the case studies: *reliability* and *resilience* of the technical infrastructure and energy use and environmental impact of the drinking water supply (Table 2). Table 5 provides a summary of the results of the subsequent research steps (see Fig. 1).

The *reliability* of the supply system is defined in this research as "the (un)likeliness of the 433 technical system to fail" (Hashimoto et al., 1982). The current technical state of the drinking 434 water production facility and the distribution infrastructure, and the complexity of the water 435 treatment are important technical sustainability criteria for the local drinking water supply 436 system. Other technical criteria that should be considered are the supply continuity of the 437 facility, which stands for the capability to meet the set legal standards for drinking water 438 supply under all circumstances, and the operational reliability, to solve technical failures 439 without disturbance of the drinking water supply. 440

Table <u>5-2</u> Summary of proposed technical sustainability characteristics, technical issueaspects from
 case studies (see <u>Tables 1-3App. A-C</u>), relevant SDG¹ indicators and <u>JMPWHO Guidelines for Drinking-</u>
 <u>Water Quality</u> (WHO, 2017a) ² issueaspects, and technical sustainability criteria.

Technical sustainability characteristics	Reliability of technical infrastructure	Resilience of technical infrastructure	Energy use and environmental impact
Sustainability	Drinking water pressure	Abstraction capacity	Energy use
issue aspects	Drinking water treatment	Treatment capacity	Environmental impact
from case	Reliability of abstraction, treatment and distribution infrastructure	Treatment methods	Additional excipients
studies		Distribution capacity	Waste water Wastewater
		Resilience of technical infrastructure	Waste materials
SDG 6 targets ¹	6.1, 6.4	6.1, 6.4	6.4

	WHO Guidelines for Drinking-Water Quality (WHO, 2017a)_HMP ²	Safely managed drinking water services, i.e. improved drinking water source on premises, available when needed and free from contamination	Resilient technologies and processes Upgrades of water treatment and storage capacity	Reliability of the energy supply Renewability of the energy
	Sustainability criteria	Technical state abstraction and treatment facility Technical state distribution infrastructure <u>C</u> omplexity of water treatment Supply continuity for customers Operational reliability	Abstraction permit compared to annual drinking water demand Production capacity compared to peak demand Flexibility of treatment method Technical innovations to improve resilience Technical investments to improve resilience	Energy use of abstraction and treatment Energy use of distribution Environmental impact (additional excipients, waste waterwastewater, waste materials) Reliability energy supply Use of renewable energy
444 445	¹ SDG = Sustainabl indicators related	e Development Goal; see App. to sustainability characteristics	V for summary of Sustainable D (UN, 2015)	evelopment Goal 6 targets and
446 447 448	² –JMP = 2017 up Hygiene(WHO and	date of the WHO/UNICEF Joir UNICEF, 2017)	nt Monitoring Programme for	Water Supply, Sanitation and
449 450	In this research	the <i>resilience</i> of the drinki	ing water supply system is	defined as "the possibility
451	to respond to s	hort- and long-term chang	es in water demand or wa	ter quality" (Hashimoto et
452	al., 1982). Clima	ate change and other deve	elopments in water dema	nd and quality call for the
453	use of more r	esilient technologies and	I processes, and may re	quire upgrades of water
454	treatment and	storage capacity (WHO and	d UNICEF, 2017). The case	s "2018 Summer drought"
455	as well as "Dr	inking water demand gro	owth" emphasise the imp	portance of the available
456	abstraction per	mits, and treatment and	distribution capacity com	pared to the annual and
457	peak water der	nand respectively for the	resilience of the local drin	king water supply system.
458	Furthermore, t	he flexibility of the treatn	nent method determines	whether a drinking water
459	supply system	can deal with variation i	n, or deterioration of wa	ter quality and emerging
460	contaminants,	the sustainability issuea	spects found in the cas	se "Groundwater quality
461	development".			

Energy use and environmental impact includes the sustainability issue<u>aspect</u>s from the cases 463 "Groundwater quality development" and "Drinking water demand growth": the energy use of abstraction, treatment and distribution, and the environmental impact of additional
excipients, waste water and other waste products of the treatment. Especially when the raw
water quality deteriorates, the required water treatment methods become more complex. In
generalgeneral, this leads to large investments, as well as an increasing energy use and
environmental impact, e.g. when advanced membrane filtration methods are required.
Additional global sustainability issueaspects are the reliability of the energy supply, and the
renewability of the energy that is used (WHO, 2017a).

471 **3.3 Socio-economic sustainability characteristics**

Three socio-economic sustainability characteristics are proposed that summarise the socioeconomic <u>issueaspect</u>s affecting the drinking water supply as found in the case studies: *drinking water availability, water governance,* and *land and water use*. Table 6 provides a summary of the results of the subsequent research steps (Table 3). (see Fig. 1).

The drinking water availability can be quantified by the percentage of households connected 476 to the drinking water supply. A sustainable local drinking water supply provides sufficient 477 drinking water of a quality that meets the national or international drinking water standards, 478 for a tariff that is affordable to all households (UN, 2015). In the Netherlands the drinking 479 water tariff by law must be built on a cost-recovery, transparent and non-discriminatory basis 480 (Dutch Government, 2009).-Water saving strategies will reduce the drinking water demand 481 growth and therefore will contribute to the sustainability. Drinking water safety is a 482 prerequisite for public health and sustainable drinking water supply. The WHO Guidelines 483 consider water safety plans-as essential to provide the basis for system protection and process 484 control to ensure water quality issues present a negligible risk to public health and that the 485 drinking water is acceptable to consumers. The Therefore JMPWHO Guidelines for Drinking-486

Water Quality (2017) monitors the availability of water safety plans (including emergency
 plans) on how to act in case of drinking water supply disturbances, shortages, or drinking
 water quality emergencies_, which are essential to ensure drinking water availability (WHO
 and UNICEF, 2017). <u>A water safety plan can be built on various safety protocols.</u>

Water governance focuses on policies and legislation, enforcement and compliance of 491 regulations. Good governance also includes decision-making processes considering different 492 stakeholder interests, to ensure accountable, transparent and participatory governance 493 (UNESCAP, 2009). The availability of (inter)national and local policies and legislation on 494 drinking water supply as well as on water management, including regulations and permits, 495 496 and the level of compliance of the drinking water supplier to these policies and legislation, are important for the socio-economic sustainability. The sustainability of local drinking water 497 supply is also characterised by the stakeholders' interests related to the presence of a local 498 drinking water abstraction, and by how local authorities weigh these interests in their 499 500 decision-making processes. A final issueaspect in water governance that reaches further than local stakeholder interests is the risk of small- or large-scale emergencies for the drinking 501 water supply caused by human activities or conflicts (WHO and UNICEF, 2017). 502

The local *land and water use*, at surface and subsurface level, affects the water quality and quantity. It may have resulted in historical contaminant sources, causing point or non-point water pollution, but it may also lead to emerging contaminants that provide new risks to water quality. Additionally, water use for other purposes may limit the availability of water resources for drinking water. Regulations to protect water quality or water quantity may cause limitations for local land and water use. Financial compensation for suffered economic damage due to the impact of the abstraction or the limitations caused by protection

36

510 regulations can be an important issue<u>aspect</u> for the sustainability of the drinking water supply

511 system.

- 512 **Table 6-3** Summary of proposed socio-economic sustainability characteristics, socio-economic
- 513 issueaspects from case studies (see Tables 1-3App. A-C), relevant SDG¹ indicators and JMP_WHO
- 514 <u>Guidelines for Drinking-Water Quality</u> (WHO, 2017a)² issue<u>aspect</u>s, and socio-economic sustainability
- 515 criteria.

Socio-economic sustainability characteristics	Drinking water availability	Water governance	Land and water use	
Sustainability	Customers	Abstraction permits	Water use	
issue<u>aspect</u>s	Drinking water availability	Drinking water standards	Land use	
from case studies	Drinking water demand	Water authorities	Agriculture	
	Drinking water tariff	Water legislation, policy and	Nature, groundwater-dependent	
	Drinking water quality	regulations	ecosystems	
	Drinking water volume	Drinking water suppliers	Financial compensation	
	Drinking water shortage	Compliance	Spatial impact	
	Emergencies, disturbances	Stakeholders		
	Water saving			
SDG 6 targets ¹	6.1	6.3, 6.4, 6.5, 6.6, 6.a, 6.b	6.3, 6.4	
WHO Guidelines	Water safety plan	Small- or large-scale	-	
for Drinking-		emergencies for the drinking		
Water Quality		human activities or conflicts		
(WHO, 2017a) <mark>JMP²</mark>				
Sustainability	Percentage connected	Availability of (drinking) water	Land use (including subsurface use)	
criteria	households	legislation and policies	Water use for other purposes tha	
	Drinking water service quality	Compliance of drinking water	drinking water	
	Drinking water tariff	supplier	Regulations on land and water use	
	Water saving strategy	Decision-making process by	Limitations to land or water use	
	Water safety plan<u>protocols</u>		Financial compensation of	
			economic damage from impact of	
		human activities or conflicts	abstraction or limitations to land	

517 indicators related to sustainability characteristics (UN, 2015)

518 519

516

213

²-JMP = 2017 update of the WHO/UNICEF Joint Monitoring Programme for Water Supply, Sanitation and
 Hygiene(WHO and UNICEF, 2017)

522 4 DConclusions and discussion

523 4.1 Use of DPSIR systems approach

In this study we used an integrated systems approach to analyse the local drinking water 524 supply system, combining hydrological, technical and socio-economic aspects of the system. 525 The analysis of the three selected cases with DPSIR supported the identification of aspects 526 that shape the sustainability of the local drinking water supply system. The case analysis did 527 indeed help to account for differences between short-term and long-term developments, and 528 for the impact of external influences that come from the national and international scale. 529 The applied DPSIR approach is a linear socio-ecological framework originally developed to 530 531 identify the impact of human activities on the *state* of the environmental system (Binder et al., 2013). However, the The integrated systems approach of the local drinking water supply 532 system is a complex system rather than linear, because the impact of a pressure to one system 533 element could present a pressure to another system element. This as adopted in this research 534 complicated the identification of pressures and impacts: the impact of a pressure to one 535 system element presented pressures to other system elements. For instance, high 536 temperatures and lack of precipitation caused a higher drinking water demand, and surface 537 water quality deterioration. Both consequently presented *pressures* with an *impact* to the 538 resilience and reliability of the technical drinking water supply infrastructure. Although this 539 hampered the analysis, the use of DPSIR supported a the-systematic analysis of the local 540 drinking water supply cases and helped to identify the sustainability issueaspects. Use of a 541 542 different integrated systems approach would not have led to a significantly different outcome of the case analysis. A next step could potentially be to use the identified system 543

544 <u>characteristics for a system dynamics analysis and modelling. However, this is beyond the</u>
 545 <u>scope of this current research.</u>

The analysis of the three selected cases with DPSIR supported the identification of issues that 546 shape the sustainability of the local drinking water supply system. This was an unconventional 547 use of DPSIR, and can be seen as a form of reverse engineering: "extracting knowledge or 548 design blueprints from anything man-made" (Eilam, 2011), in this case from a local drinking 549 water supply system. The results of the research show that DPSIR can be used to extract 550 knowledge on the characteristics of a complex system. According to Pahl-Wostl (2015)-DPSIR 551 can be used to analyse the temporal and spatial dimensions of complex, multi-level 552 environmental problems such as water resources management. This includes the complex 553 system of local drinking water supply, which was analysed in this study. The case analysis did 554 indeed help to account for differences between short-term and long-term developments, and 555 for the impact of external influences that come from the national and international scale. 556

557 **4.2 General applicability of the sustainability characteristics**

To increase the general applicability of the results from the analysis of the Dutch cases on drinking water supply, the identified sustainability <u>issueaspect</u>s were related to worldwide acknowledged sustainability <u>issueaspect</u>s, by cross-checking <u>the targets set in the SDG 6 (UN,</u> 2015), and the JMP (WHO and UNICEF, 2017)<u>with international policies on drinking water</u> supply. This put the <u>issueaspect</u>s in a broader perspective, which may contribute to the transferability of the proposed sustainability characteristics and criteria to other areas.

Assessments to understand the sustainability challenges as well as the impact of future developments and adaptation options are seen as powerful tools for policy making (Ness et al., 2007, Singh et al., 2012). Examples of sustainability assessments that relate to drinking

567 water supply are the Sustainable Society Index (Van der Kerk and Manuel, 2008), the "EBC Performance Assessment Model" model (European Benchmarking Co operation, 2017), the 568 International Water Association Performance Indicator System (Alegre et al., 2006a), the 569 Groundwater Footprint (Gleeson and Wada, 2013) and the City Blueprint (Van Leeuwen et al., 570 2012). Although these assessments include criteria that are relevant for sustainable drinking 571 water supply on various spatial and organizational scales, they do not consider drinking water 572 supply on a local scale. The sustainability characteristics as proposed in this research may be 573 used to develop a sustainability assessment for the local drinking water supply system, that 574 can help to identify sustainability challenges and trade-offs of adaptation strategies. Trade-off 575 analysis supports decision-making processes and makes these processes more transparent to 576 local stakeholders (Hellegers and Leflaive, 2015). Based on the local situation and data 577 578 availability, adequate indicators and indices can be selected to quantify the sustainability 579 characteristics in a certain area (Van Engelenburg et al., 2019).

580 **<u>5</u>** Conclusions

The aim of this study was to identify a set of characteristics that describeing the sustainability 581 of a local drinking water supply system in the Netherlands to support policy- and decision-582 making on sustainable drinking water supply. The use of the DPSIR systems approach was an 583 adequate method for the analysis of the cases. The results of the analysis of the three cases 584 585 confirmed the hypothesis that sustainability is contextual, resulting in different sustainability aspects in the various cases. The combined results of the analysis of three different practice 586 cases contributed to a better understanding of identification of the drinking water supply in 587 the Netherlands. sustainability characteristics. The use of the DPSIR systems approach was an 588 adequate method for the Cross-checking of the results of case analysis with international 589

590 policies on drinking water supply provided a wider context than the Netherlands and has thus
 591 contributed to the general applicability of the identified sustainability characteristics.

Based on the presented analysis, the following set of hydrological, technical and socioeconomic sustainability characteristics is proposed, respectively: (1) *water quality, water resource availability,* and *impact of drinking water abstraction;* (2) *reliability* and *resilience of the technical system,* and *energy use and environmental impact;* (3) *drinking water availability, water governance,* and *land and water use.* <u>Elaboration of the sustainability characteristics</u> <u>into more detailed criteria may further increase the value of the results of this research in the</u>

598 process of development of policies on sustainable drinking water supply in the Netherlands.

599 Data availability: The source data used for the illustrations of the cases are available at600 request.

601 Author Contributions: Conceptualization J.v.E., P.J.G.J.H., E.v.S.; methodology J.v.E.,

P.J.G.J.H., E.v.S.; data curation J.v.E.; investigation J.v.E.; writing – original draft preparation

J.v.E.; writing – review and editing J.v.E., P.J.G.J.H., E.v.S., A.J.T., R.U.; visualization J.v.E.;

supervision P.J.G.J.H., E.v.S., A.J.T., R.U. (See CRediT taxonomy for term explanation).

Acknowledgments: We are indebted to <u>Vitens staff</u> Maarten Fleuren and Martin de Jonge (Vitens) for their data collection for the illustrations of the analysed drinking water supply cases, and to <u>Vitens staff</u> Mark de Vries, Henk Hunneman and Rian Kloosterman (Vitens) for cross-checking the results of the case analysis.<u>We thank the two anonymous referees for their</u> <u>comments that helped to further improve the manuscript.</u>

610 **Conflicts of Interest:** The first author performed the research partially in time funded by 611 Vitens, where she is employed. She had carte blanche for the content of the research.

613 **References**

612

- ALEGRE, H., BAPTISTA, J. M., CABRERA JR, E., CUBILLO, F., DUARTE, P., HIRNER, W., MERKEL, W. & PARENA,
 R. 2006a. *Performance indicators for water supply services*, IWA publishing.
- ALEGRE, H., BAPTISTE, J. M., CABRERA, E., JR., CUBILLO, F., DUARTE, P., HIRNER, W., MERKEL, W. &
 PARENO, R. 2006b. Performance Indicators for Water Supply Services. *Manual of Best Practice*.
 London: IWA Publishing.
- BAGGELAAR, P. K. & GEUDENS, P. J. J. G. 2017. Prognoses en scenario's drinkwatergebruik in Nederland
 (Prognoses and scenarios for drinking water use in the Netherlands). *In:* ICASTAT (ed.). The Hague,
 the Netherlands: VEWIN.
- BAUER, J. M. & HERDER, P. M. 2009. Designing Socio-Technical Systems. *Philosophy of Technology and Engineering Sciences.* Amsterdam: North-Holland.
- 624 BINDER, C. R., HINKEL, J., BOTS, P. W. G. & PAHL-WOSTL, C. 2013. Comparison of frameworks for analyzing 625 social-ecological systems. *Ecology and Society*, 18, 26-45.
- 626 BRATTEBØ, H., ALEGRE, H., CABRERA, E., MARQUES, R., HEIN, A. & CRUZ, C. 2013. A master framework for 627 UWCS sustainability.
- 628 CARR, E. R., WINGARD, P. M., YORTY, S. C., THOMPSON, M. C., JENSEN, N. K. & ROBERSON, J. 2009. Applying 629 DPSIR to sustainable development. *INT J SUST DEV WORLD*, 14, 543-555.
- 630 COHEN, D. A. 2016. The Rationed City: The Politics of Water, Housing, and Land Use in Drought-Parched São 631 Paulo. *Public Culture*, 28, 261-289.
- 632 DUTCH GOVERNMENT 2009. Drinkwaterwet (Dutch Drinking water Decree). *BWBR0026338*. The Hague.
- 633 EILAM, E. 2011. Reversing: secrets of reverse engineering, John Wiley & Sons.
- EKINS, P., GUPTA, J. & BOILEAU, P. 2019. Global Environment Outlook GEO-6: Healthy Planet, Healthy People.
 Global Environment Outlook. Cambridge: United Nations Environment Programme.
- EUROPEAN BENCHMARKING CO-OPERATION 2017. Learning from international best practices; 2017 Water and
 Wastewater Benchmark. The Hague, Netherlands: EBC.
- EUROPEAN ENVIRONMENT AGENCY 2018. European waters Assessment of status and pressures 2018.
 Luxembourg.
- 640 EUROPEAN UNION 2000. EU Water Framework Directive. *In:* EUROPEAN UNION (ed.) Official Journal of the 641 European Communities ed.
- EUROSTAT 1999. Environmental indicators: Typology and overview. *Technical Report NO. 25.* Copenhagen:
 European Environment Agency.
- 644 GLEESON, T. & WADA, Y. 2013. Assessing regional groundwater stress for nations using multiple data sources 645 with the groundwater footprint. *ENVIRON RES LETT*, 8, 044010.
- HASHIMOTO, T., STEDINGER, J. R. & LOUCKS, D. P. 1982. Reliability, Resiliency, and Vulnerability Criteria For
 Water Resource System Performance Evaluation. WATER RESOUR RES, 18, 14-20.
- 648 HELLEGERS, P. & LEFLAIVE, X. 2015. Water allocation reform: what makes it so difficult? *WATER INT*, 40, 273-649 285.
- 650JANŽA, M. 2015. A decision support system for emergency response to groundwater resource pollution in an651urban area (Ljubljana, Slovenia). ENVIRON EARTH SCI, 73, 3763-3774.
- 652JØRGENSEN, L. F. & STOCKMARR, J. 2009. Groundwater monitoring in Denmark: Characteristics, perspectives653and comparison with other countries. HYDROGEOL J, 17, 827-842.
- 654 KOOLS, S., VAN LOON, A., SJERPS, R. & ROSENTHAL, L. 2019. The quality of drinking water resources in the 655 Netherlands. *In:* KWR (ed.) *KWR Report.* Nieuwegein, the Netherlands: KWR.
- LIU, J., MOONEY, H., HULL, V., DAVIS, S. J., GASKELL, J., HERTEL, T., LUBCHENCO, J., SETO, K. C., GLEICK,
 P., KREMEN, C. & LI, S. 2015. Sustainability. Systems integration for global sustainability. *Science*,
 347, 1258832.
- LOUCKS, D. P. 2000. Sustainable Water Resources Management. WATER INT, 25, 3-10.
- LOUCKS, D. P., VAN BEEK, E., STEDINGER, J. R., DIJKMAN, J. P. & VILLARS, M. T. 2017. Water resource
 systems planning and management: an introduction to Methods, Models and Applications, Cham,
 Switzerland, Springer, Deltares and UNESCO-IHE.
- MELESE, Y. G., HEIJNEN, P. W., STIKKELMAN, R. M. & HERDER, P. M. 2015. Exploring for real options during
 CCS networks conceptual design to mitigate effects of path-dependency and lock-in. *INT J GREENH GAS CON*, 42, 16-25.
- MENDIZABAL, I., BAGGELAAR, P. K. & STUYFZAND, P. J. 2012. Hydrochemical trends for public supply well
 fields in The Netherlands (1898-2008), natural backgrounds and upscaling to groundwater bodies. J
 HYDROL, 450-451, 279-292.
- MINISTRY OF INFRASTRUCTURE AND ENVIRONMENT & MINISTRY OF ECONOMIC AFFAIRS AND CLIMATE
 POLICY 2019. Nederland beter weerbaar tegen droogte; Eindrapportage Beleidstafel Droogte (The
 Netherlands more resilient to drought; final report policy table drought). The Hague, the Netherlands.
- 672 NAPOLI, C. & GARCIA-TELLEZ, B. 2016. A framework for understanding energy for water. *INT J WATER* 673 *RESOUR D*, 32, 339-361.
- NESS, B., URBEL-PIIRSALU, E., ANDERBERG, S. & OLSSON, L. 2007. Categorising tools for sustainability
 assessment. *Ecological Economics*, 60, 498-508.
- PAHL-WOSTL, C. 2002. Towards sustainability in the water sector The importance of human actors and
 processes of social learning. *AQUAT SCI*, 64, 394-411.

- 678 PAHL-WOSTL, C. 2015. Water Governance in the Face of Global Change; From understanding to 679 transformation, Springer. 680 PANT, L. P., ADHIKARI, B. & BHATTARAI, K. K. 2015. Adaptive transition for transformations to sustainability in 681 developing countries. CURR OPIN ENV SUST, 14, 206-212. 682 SINGH, R. K., MURTY, H. R., GUPTA, S. K. & DIKSHIT, A. K. 2012. An overview of sustainability assessment 683 methodologies. ECOL INDIC, 15, 281-299. 684 SMITH, A. & STIRLING, A. 2010. The Politics of Social-ecological Resilience and Sustainable Socio-technical 685 Transitions. ECOL SOC, 15, 11. SORENSEN, P. 2017. The chronic water shortage in Cape Town and survival strategies. INT J ENVIRON STUD, 686 74**,** 515-527. 687 TEULING, A. J. 2018. A hot future for European droughts. NAT CLIM CHANGE, 8, 364-365. 688 689 UN 2007. Indicators of Sustainable Development: Guidelines and Methodologies. Economic & Social Affairs, New 690 York: United Nations. 691 UN 2015. Transforming our world: The 2030 Agenda for Sustainable Development. United Nations. 692 UN 2018. Sustainable Development Goal 6 Synthesis Report 2018 on Water and Sanitation. In: WATER, U. 693 (ed.). New York, USA: United Nations. 694 UNESCAP 2009. Economic and social survey of Asia and the Pacific 2009; Addressing triple threats to 695 development. In: UNITED NATIONS ECONOMIC AND SOCIAL COMMISSION FOR ASIA AND THE 696 697 PACIFIC (ed.) ST/ESCAP/2522 ed. Bangkok, Thailand: United Nations Economic and Social Commission for Asia and the Pacific,. 698 699 UNICEF & WHO 2015. Progress on Sanitation and Drinking Water; 2015 Update and MDG Assessment. NLM classification: WA 670 ed.: UNICEF and World Health Organization. 700 VAN DEN BRINK, C. & WUIJTS, S. 2016. Towards an effective protection of groundwater resources: putting policy into practice with the drinking water protection file. *Water Policy*, 18, 635-653. VAN DER AA, N. G. F. M., TANGENA, B. H., WUIJTS, S. & DE NIJS, A. C. M. 2015. Scenario's drinkwatervraag 701 702 703 2015-2040 en beschikbaarheid bronnen; verkenning grondwatervoorraden voor drinkwater (Scenarios 704 drinking water demand 2015-2040 and water resources availability; exploratory study on groundwater 705 resources for drinking water). In: RIVM (ed.). Bilthoven. 706 VAN DER KERK, G. & MANUEL, A. 2008. A comprehensive index for a sustainable society: The SSI - the 707 Sustainable Society Index. ECOL ECON, 66, 228-242. 708 VAN ENGELENBURG, J., DE JONGE, M., RIJPKEMA, S., VAN SLOBBE, E. & BENSE, V. F. 2020a. Hydrogeological 709 evaluation of managed aquifer recharge in a glacial moraine complex using long-term groundwater 710 data analysis Hydrogeology Journal. 711 VAN ENGELENBURG, J., FLEUREN, M. & DE JONGE, M. 2020b. Drinking water production data 2018-2020 and 712
- groundwater quality data 1985-2020 (unpublished). In: VITENS (ed.). Vitens. 713 VAN ENGELENBURG, J., HUETING, R., RIJPKEMA, S., TEULING, A. J., UIJLENHOET, R. & LUDWIG, F. 2017. 714 Impact of Changes in Groundwater Extractions and Climate Change on Groundwater-Dependent 715 Ecosystems in a Complex Hydrogeological Setting. WATER RESOUR MANAG, 1-14.
- 716 VAN ENGELENBURG, J., VAN SLOBBE, E. & HELLEGERS, P. 2019. Towards sustainable drinking water 717 abstraction: an integrated sustainability assessment framework to support local adaptation planning. J 718 INTEGR ENVIRON SCI, 16, 89-122.
- 719 VAN LEEUWEN, C. J., FRIJNS, J., VAN WEZEL, A. & VAN DE VEN, F. H. M. 2012. City Blueprints: 24 Indicators 720 to Assess the Sustainability of the Urban Water Cycle. WATER RESOUR MANAG, 26, 2177-2197.
- 721 VAN NOORDWIJK, M., SPEELMAN, E., HOFSTEDE, G. J., FARIDA, A., ABDURRAHIM, A. Y., MICCOLIS, A., 722 HAKIM, A. L., WAMUCII, C. N., LAGNEAUX, E., ANDREOTTI, F., KIMBOWA, G., ASSOGBA, G. G. C., BEST, L., TANIKA, L., GITHINJI, M., ROSERO, P., SARI, R. R., SATNARAIN, U., ADIWIBOWO, S., LIGTENBERG, A., MUTHURI, C., PEÑA-CLAROS, M., PURWANTO, E., VAN OEL, P., ROZENDAAL, D. 723 724 725 SUPRAYOGO, D. & TEULING, A. J. 2020. Sustainable Agroforestry Landscape Management: Changing 726 the Game. Land, 9.
- 727 VAN THIEL, L. 2017. Watergebruik thuis 2016 (Domestic water use 2016) [Online]. Amsterdam, The 728 Netherlands: TNS Nipo. [Accessed C8732 C8732 | juli 2017].
- VITENS 2016. Resiliently ahead; Long-term vision on our infrastructure 2016-2040. Zwolle, The Netherlands: 729 730 Vitens.
- 731 WHO 2017a. Guidelines for drinking-water quality: fourth edition incorporating the first addendum. Geneva: 732 733 World Health Organization.
- WHO 2017b. Safely managed drinking water thematic report on drinking water 2017. Geneva, Switzerland: 734 World Health Organization.
- WHO & UNICEF 2017. Progress on drinking water, sanitation and hygiene, 2017 update and SDG Baselines. 735 736 Geneva: World Health Organization (WHO) and UNICEF.
- WOLTERS, H. A., VAN DEN BORN, G. J., DAMMERS, E. & REINHARD, S. 2018. Deltascenario's voor de 21e 737 738 eeuw, actualisering 2017 (Delta scenarios for the 21st century, actualisation 2017). Utrecht: Deltares.
- 739

740

Appendix A Results <u>of</u> analysis case 1 "2018 Summer drought"

Table A.1 Summary of impact, short-term and long-term response and sustainability *issueaspects* in case 1 "2018 Summer drought" (for complete results of the case study see Table A.2).

Impact	Short-term response	Long-term response	Sustainability issue<u>aspect</u>s
Extreme drinking water use, high drinking water demand.	Drinking water suppliers increased abstraction volume.	Development of water saving strategies.	Drinking water use, drinking water demand, drinking water suppliers, abstraction volumes, water saving.
Drought, falling water discharges and groundwater levels, damage to groundwater-dependent ecosystems and agriculture.	Water use limitations, water authorities applied existing drought water policy, risk for water quality.	Development of additional water shortage policy for water management and water governance.	Drought, water discharge, groundwater levels, groundwater- dependent ecosystems, agriculture, water use, water authorities, water policy, water management, water governance, water availability.
Customers worried about drinking water availability.	Drinking water suppliers called upon customers for drinking water saving.	Societal support for drinking water saving strategies.	Customers, drinking water availability, drinking water suppliers, water saving.
Declining surface water discharge and quality.	Drinking water supplies took measures to safeguard raw water quality.	Development of additional policies on water quality protection.	Surface water discharge, surface water quality, drinking water suppliers, raw water quality, water management policies, water use.
Groundwater quality deterioration.	No response possible due to lack of water.	Development of additional policies on water quality protection.	Groundwater quality, surface water quality, water shortage, surface water discharge, water management policies
Drinking water quality at risk due to rising water temperature in pipelines.	Sufficient refreshment due to high demand.	Changing the design standard of distribution pipelines to limit risk of temperature rise.	Drinking water quality, treatment method, distribution infrastructure.
Increasing abstraction volume, resulting in increasing impact to land use.	Stakeholder complaints by agriculture and nature.	Increased societal pressure on reduction of impact of drinking water abstraction.	Drinking water demand, abstraction volume, impact of abstraction, land use, stakeholders, agriculture, nature, drinking water suppliers.
Exceedance of abstraction permits, limiting the resilience of the technical infrastructure.	Enforcement procedures by legal authorities.	Extension of drinking water abstraction permits and water saving strategies.	Drinking water demand, abstraction volume, abstraction capacity, abstraction permit, resilience of abstraction, legal authorities, water regulations, water legislation, drinking water saving.
Shortage of drinking water during peak demand due to insufficient resilience of treatment infrastructure.	Reduced drinking water supply volume.	Adjustment of resilience and reliability of treatment infrastructure.	Treatment volume, treatment capacity, drinking water shortage, reliability of the treatment, resilience of the treatment, drinking water standards, drinking water demand, drinking water suppliers.
Insufficient distribution capacity	Lowering drinking water pressure to reduce drinking water volume	Adjustment of resilience and reliability of distribution infrastructure.	Distribution capacity, resilience and reliability of distribution, drinking water suppliers, drinking water volume, drinking water standards.
Major disturbances could cause a serious disruption of the supply.	Maximum personnel deployment by drinking water suppliers.	Investments to improve resilience and reliability of technical infrastructure by drinking water suppliers.	Drinking water demand, reliability of technical infrastructure, drinking water suppliers.

Impact	Short-term response	Long-term response	Sustainability issue<u>aspect</u>s
High energy use and environmental impact of extreme drinking water production	-	Incorporating impact to energy use and environmental impact in design of measures to improve regilipped and reliability of technical	Drinking water demand, energy use, environmental impact, drinking water suppliers.
		infrastructure.	

Table A.2 Results analysis of Case 1 "2018 summer drought". For each pressure the response and impacts to the state of the local drinking water supply system are described. The sustainability aspects in the case are displayed in bold. The grey cells refer to Table A.1.

Driver	Pressure	Impact	Short-term response	Long-term response	Sustainability aspects
Extreme	High	Extreme drinking water use, high drinking	Drinking water suppliers increased	Development of water saving strategies.	Drinking water use,
weather	temperature,	water demand.	abstraction volume.		drinking water demand,
event	high evaporation,	The summer affected the drinking water	Drinking water suppliers increased the	The drought (re-)initiated a discourse on	drinking water suppliers,
	no precipitation	use: filling swimming pools, watering	abstraction volume to meet the	water saving strategies, including	abstraction volume, water
		gardens, extra showering all together led	increased drinking water demand.	controversial measures such as progressive	saving.
		to a very high drinking water demand .		drinking water tariffs and differentiation in	
		Additionally, there also were requests		high-grade (household and sanitation, food	
		from concerned citizens for applying		production) and low-grade (pools, gardens,	
		drinking water to refill ponds that fell dry		process water) use.	
		due to the extreme drought.			
Extreme	High	Drought, falling water discharges and	Water use limitations, water authorities	Development of additional water shortage	Drought, water discharge,
weather	evaporation, no	groundwater levels, damage to	applied existing drought water policy, risk	policy for water management and water	groundwater levels,
event	precipitation	groundwater-dependent ecosystems and	for water quality.	governance.	groundwater-dependent
		agriculture.			ecosystems, agriculture,
		The drought caused falling water	Limitations to water use from water	Discourse and policy development on water	water use, water
		discharges and groundwater levels: river	system. Water authorities applied the	management and water governance aiming	authorities, water policy,
		discharges declined, springs and brooks	special water policy that was developed	at a further prioritisation and limitations of	water management,
		fell dry, and vegetation withered or even	for periods with low water availability.	water use during water shortage, and	water governance, water
		died due to low groundwater levels and	Drinking water supply has a high ranking	retention of surface water and groundwater	availability.
		high temperatures. Groundwater-	because of its high societal relevance.	during periods with sufficient water	
		dependent ecosystems such as wetlands	In some ecologically vulnerable areas,	availability.	
		as well as agriculture produce suffered	there is a water policy to resolve local		
		from the drought.	surface water shortages by		
			supplementing from larger water bodies		
			such as rivers. This affects the local		
			surface water quality and may also affect		
			the groundwater quality.		

Driver	Pressure	Impact	Short-term response	Long-term response	Sustainability aspects
Extreme weather	High evaporation, no	Customers worried about drinking water availability.	Drinking water suppliers called upon customers for drinking water saving.	Societal support for drinking water saving strategies.	Customers, drinking water availability,
event	precipitation	Because of the visible damage to vegetation due to the drought, customers started to worry about the drinking water availability.	Drinking water suppliers communicated that there still was sufficient drinking water, but people were asked to spread the drinking water use to reduce the peak demand. Later that summer customers were called for water saving.	The drought raised awareness under customers that there are limits to the drinking water availability , thus creating (some) societal support for (drinking) water saving.	drinking water suppliers, water saving.
Extreme	No precipitation	Declining surface water discharge and	Drinking water supplies took measures to	Development of additional policies on water	Surface water discharge,
event		Due to the lack of rain, the share of industrial waste-water and treated sewage water to the surface water discharge increased, which caused the water quality in surface waters deteriorated.	Drinking water suppliers that use surface water as resource took measures to safeguard the raw water quality.	The surface water discharge and quality problems may induce development of water management policies that aim to reduce the impact of treated sewage and industrial wastewater, by reduction of water use or improvement of treatment.	drinking water suppliers, raw water quality, water management policies, water use.
Extreme	Declining surface	Groundwater quality deterioration.	No response possible due to lack of	Development of additional policies on water	Groundwater quality,
event	water quality	The impact of an incidental warm and dry summer to the groundwater quality is limited, but when comparable droughts will happen frequently the groundwater quality may deteriorate due to the impact of a declining surface water quality .	In some surface water bodies refreshment was required to guard the surface water quality , but due to the lack of precipitation there was a water shortage , so insufficient water was available for this refreshment.	The fact that surface water discharge and quality may affect- groundwater quality supports the need of water management policies that aim to refresh water bodies and to reduce the impact of treated sewage and industrial waste-water.	water shortage, surface water shortage, surface water discharge, water management policies.
Extreme weather event	High temperature	Drinking water quality at risk due to rising water temperature in pipelines. The extreme temperatures led to an increased surface water temperature, and soil temperature, that may have affected drinking water temperature in distribution infrastructure. This introduces a drinking water quality risk.	Sufficient -refreshment due to high demand. When surface water is the main resource for drinking water, the water quality risk will be limited by a treatment method that ensures the bacteriological quality of the drinking water. Sufficient refreshment within storage and high stream velocities in pipelines reduce the risk of temperature rise in the distribution infrastructure.	Changing the -design standard of distribution pipelines to limit risk of temperature rise. The risk of drinking water quality aspects caused by increased drinking water temperature due to climate change may have consequences for the design of the distribution infrastructure .	Drinking water quality, treatment method, distribution infrastructure.
	High drinking water demand	Increasing abstraction volume, resulting in increasing impact on land use.	Stakeholder complaints by agriculture and nature.	Increased societal pressure on reduction of impact of drinking water abstraction.	Drinking water demand, abstraction volume,

Driver	Pressure	Impact	Short-term response	Long-term response	Sustainability aspects
Extreme weather event		To meet the high drinking water demand , the abstraction volume rose to a high level. In some local areas the impact of the abstraction added up with the extreme drought and high temperatures, affecting the land use .	Stakeholders on agriculture and nature complained about the impact of the extra abstraction to their land use.	The drought impact enlarged the societal pressure to drinking water suppliers to reduce the impact of local drinking water abstraction to the water system.	impact of abstraction, land use, stakeholders, agriculture, nature, drinking water suppliers.
Extreme weather event	High drinking water demand	Exceedance of abstraction permits, limiting the resilience of the technical infrastructure.	Enforcement procedures by legal authorities.	Extension of drinking water abstraction permits and water saving strategies.	Drinking water demand, abstraction volume, abstraction capacity,
		To meet the high drinking water demand , the abstraction volume rose to a high level. The available abstraction capacity combined with the high abstraction volumes led to exceedance of the abstraction permits . Some local drinking abstractions exceeded the monthly permitted volume, and some abstractions even exceeded the yearly permitted volume, failing drinking water regulations. This compromised the resilience of the abstractions .	Legal authorities (provinces and water boards) started enforcement procedures to meet the water regulations. The legal authority urged the drinking water supplier to stay within these limits. However, the drinking water legislation also had to be met to ensure continuous supply of good quality drinking water at all times.	The exceedance of abstraction permit limits set off enforcement actions by the government, resulting in an increased need for additional abstraction permits , as well as drinking water saving strategies to reduce the drinking water demand .	abstraction permit, resilience of abstraction, legal authorities, water regulations, water legislation, drinking water saving.
Extreme weather event	High peak demand for drinking water	Shortage of drinking water during peak demand due to Insufficient resilience of treatment infrastructure.	Reduced drinking water supply volume.	Adjustment of resilience and reliability of treatment infrastructure.	Treatment volume, treatment capacity, drinking water shortage,
		To meet the high peak demand, the treatment volume rose to a high level. In some parts of the drinking water supply there was insufficient treatment capacity, causing a temporary shortage of drinking water during peak demand, compromising the reliability of the treatment. These limitations showed that the treatment is not resilient for this extreme peak demand.	There is no response available when the treatment capacity is insufficient, except reducing the drinking water supply volume. Exceeding the treatment capacity (by e.g. increasing the filter flow velocity or reducing the cleansing frequency of the filters) would introduce the risk of not meeting the drinking water standards.	The drought identified various locations in the technical infrastructure where the treatment capacity was not reliable at peak drinking water demand , which set drinking water suppliers off to solve these local treatment aspects. To adjust all aspects will take several years.	reliability of the treatment, resilience of the treatment, drinking water standards, drinking water demand, drinking water suppliers.
Extreme	High peak demand for	Insufficient distribution capacity.	Lowering drinking water pressure to	Adjustment of resilience and reliability of	Distribution capacity,
event	drinking water	In some parts of the drinking water supply there was insufficient distribution	To reduce the drinking water volume that was supplied, drinking water suppliers	The drought identified locations in the technical infrastructure where the	distribution, drinking water suppliers, drinking

Driver	Pressure	Impact	Short-term response	Long-term response	Sustainability aspects
		capacity due to hydraulic limitations, insufficient storage capacity, or age and quality of the pipelines. In some areas this caused unintended low drinking water pressures. These limitations put the reliability of the distribution under pressure and showed that the distribution capacity was not resilient for this extreme peak demand.	lowered the drinking water pressure intendedly in some areas. The impact of this pressure reduction is a decreased drinking water volume from taps. By reducing drinking water pressurepressure, the distributed drinking water volume was reduced, however this also led to falling short of the mandatory drinking water standards in some areas.	distribution capacity was not reliable at peak demand, which set drinking water suppliers off to solve these local distribution aspects. To adjust all aspects will take several years.	water volume, drinking water standards.
Extreme weather event	High peak demand for drinking water	Major disturbances could cause a serious disruption of the supply.	Maximal personnel deployment by drinking water suppliers.	Investments to improve resilience and reliability of technical infrastructure by drinking water suppliers.	Drinking water demand, reliability of technical <u>ii</u> nfrastructure, drinking
		The high peak demand required a maximal exploitation of the technical infrastructure . To ensure the reliability of the drinking water supply , many parts of the infrastructure are designed redundant, which limits the impact of disturbances for customers. However, a major disturbance in the infrastructure, such as failure of a large transportation pipeline, could have led to disruption of the supply, because the resilience was limited due to limited reserve capacity and reduced maintenance during the extreme drinking water demand period.	To ensure the reliability of the drinking water supply , disturbances are always solved with priority. During the extreme peak period drinking water suppliers had all personnel put on standby to immediately solve any disturbances.	The drought identified locations in the technical infrastructure where not reliable at peak demand , which set drinking water suppliers off to solve these local aspects, and where necessary create redundancy to decrease the risk of disturbances, and thus improve the reliability .	water suppliers.
Extreme	High peak	High energy use and environmental	-	Incorporating impact on energy use and	Drinking water demand,
event	drinking water	production.		to improve resilience and reliability of technical infrastructure.	environmental impact, drinking water suppliers.
		The magnitude and duration of the peak demand forced a maximal exploitation of the technical infrastructure, causing a maximal energy use and environmental impact .	There was no short-term response available to reduce the energy use and environmental impact.	The drought identified locations in the technical infrastructure where not reliable at peak demand , which set drinking water suppliers off to solve these local aspects. Energy use and environmental impact are important aspects that are considered in the design of the solutions for these aspects.	

Appendix B Results <u>of</u> analysis case 2 "Groundwater quality development"

Table B.1 Summary of impact, short-term and long-term response and sustainability aspects in case 2, "Groundwater quality development" (for complete results of the case study see Table B.2).

Impact	Short-term response	Long-term response	Sustainability aspects
Surface water quality deteriorates due to limited surface water discharge.	Monitoring and evaluation of water quality development.	Water legislation on water quality and quantity protection, drinking water savings strategies.	Surface water quality, surface water discharge, monitoring and evaluation, water legislation, water quality and quantity, drinking water saving.
Groundwater quality deteriorates due to deteriorating surface water quality.	Monitoring and evaluation of water quality development.	Improvement of sewage and waste- water treatment, and water saving strategies.	Groundwater quality, surface water quality, monitoring and evaluation, water saving.
Soil energy systems may affect groundwater quality.	Monitoring and evaluation of water quality development, research.	Groundwater protection regulations.	Groundwater quality, groundwater pollution, research, monitoring and evaluation, regulations, groundwater quality protection.
Local and upstream land and water use affects the surface water quality.	Monitoring and evaluation of water quality development.	Policy and measures to meet water legislation to protect and improve water quality and quantity.	Surface water quality, land and water use, contaminants, monitoring and evaluation, water legislation, water quantity.
Diffuse and point sources of pollution affect surface water and groundwater quality.	Monitoring and evaluation of water quality development.	Measures to remove historical sources of pollution and to prevent new sources of pollution.	Groundwater quality, nutrients, organic micro-pollutants, other contaminants, surface water quality, monitoring and evaluation, water legislation, water quality protection.
Emerging contaminants in surface and groundwater require new drinking water treatment methods.	Enforcement of groundwater protection regulations on pollution incidents and monitoring and evaluation.	Development of treatment methods to remove emerging contaminants from sewage, industrial waste-water and/or drinking water.	Emerging contaminants, groundwater quality, surface water quality, resilience and reliability of the drinking water treatment, groundwater protection, land and water use, water legislation, sources of pollution, drinking water treatment methods, energy use, environmental impact, drinking water tariff.
Land use (change) may cause groundwater quality deterioration.	Enforcement of groundwater protection regulations on land use change and monitoring and evaluation.	Combination of extensive land use functions with drinking water abstraction.	Land use change, groundwater quality, sources of pollution, groundwater protection regulations, water use, enforcement of regulations, monitoring and evaluation, drinking water abstraction, extensive land use, nature, agriculture, water system.
Surface water and groundwater quality deterioration determine the required drinking water treatment.	Monitoring of drinking water quality, in case of emergencies measures are taken to safeguard the drinking water quality.	Adjustment of treatment methods to be able to continue to meet the drinking water standards.	Raw water quality, drinking water standards, water quality, vulnerability of the water system for contamination, treatment methods, reliability and resilience of treatment, drinking water quality, emergencies, energy use, environmental impact, drinking water tariff.
Variations in raw water quality can only be handled if treatment method is resilient to these variations.	Monitoring and evaluation of water quality development.	Increase of resilience and reliability of drinking water treatment.	Surface water quality, groundwater quality, resilience and reliability of the treatment, monitoring and evaluation, raw water quality, energy use, environmental impact, drinking water tariff.

Table B.2 Results analysis of Case 2 "Groundwater quality development". The- sustainability *issueaspects* in this case are displayed in bold. The grey cells refer to Table B.1.

Drivers	Pressure	Impact	Short-term response	Long-term response	Sustainability aspects
Changing climate variability	Less summer precipitation, higher summer	Surface water quality deteriorates due to limited surface water discharge.	Monitoring and evaluation of water quality development.	Water legislation on water quality and quantity protection and drinking water savings strategies.	Surface water quality, surface water discharge, monitoring and
	temperatures	In summer surface water quality deteriorates due to limited surface water discharge, combined with increasing contribution of industrial and treated sewage water recharges compared to natural discharges due to lack of summer precipitation.	Monitoring and evaluation of water quality development is necessary to be able to timely respond to a changing surface water quality.	Land and water use must meet water legislation as set by the European Water Framework Directive and national water legislation to protect and improve water quality and quantity. Further improvement of sewage and wastewater treatment will reduce the impact on the surface water quality. Drinking water saving strategies can also lead to reduction of treated sewage water recharges and industrial recharges.	evaluation, water legislation, water quality and quantity, drinking water saving.
Changing climate variability	Surface water quality deterioration	Groundwater quality deteriorates due to deteriorating surface water quality. Groundwater quality may be affected by the deteriorating surface water quality during	Monitoring and evaluation of water quality development. Monitoring and evaluation of water quality development is necessary to be able to timely respond to a changing	Improvement of sewage and wastewater treatment, and water saving strategies. Further improvement of sewage and wastewater treatment will reduce the impact on the surface water quality . (Drinking) water	Groundwater quality, surface water quality, monitoring and evaluation, water saving.
		summer periods through natural or artificial infiltration of surface water.	surface water quality.	saving strategies can also lead to reduction of treated sewage water recharges and industrial recharges.	
Socio- economic developments	Increase in use of soil energy systems	Soil energy systems may affect groundwater quality. There is a transition going on towards renewable energy resources, not only wind and solar energy but also towards use of soil energy. Groundwater quality may be affected by the use of soil	Monitoring and evaluation of water quality development, research. Research on, and monitoring and evaluation of the impact of soil energy to the groundwater quality (including temperature impact) is necessary to avoid introduction of new sources of pollution by soil energy systems.	Groundwater protection regulations. Regulations on soil energy help to limit the risk for groundwater quality. Policy is developed to exclude vulnerable groundwater systems that are used for drinking water supply for soil energy use for groundwater quality protection.	Groundwater quality, groundwater pollution, research, monitoring and evaluation, regulations, groundwater quality protection.
		energy, due to risk of groundwater pollution by soil energy systems			

Drivers	Pressure	Impact	Short-term response	Long-term response	Sustainability aspects
		and the risk of leakage through aquitards that protect aquifers.			
Population growth, industrial	Increasing sewage and wastewater	Local and upstream land and water use affects the surface water quality.	Monitoring and evaluation of water quality development.	Policy and measures to meet water legislation to protect and improve water quality and quantity.	Surface water quality, land and water use, contaminants, monitoring
developments discharges		Surface water quality is affected by local and upstream land and water use activities. Discharge of treated sewage water as well as industrial wastewater discharges introduce contaminants in the water system.	Monitoring and evaluation of the water quality development is necessary to be able to timely respond to a changing surface water quality.	Land and water use must meet water legislation as set by the European Water Framework Directive and national water legislation to protect and improve water quality and quantity. According to the water legislation in the European Water Framework Directive additional measures must be taken to reach the set goals in 2027.	and evaluation, water legislation, water quantity.
Population growth, industrial developments	Historical pollution, increasing sewage and wastewater discharges (change)	Diffuse and point sources of pollution affect surface water and groundwater quality. Groundwater quality is affected by diffuse and point sources of pollution, such as nutrients, organic micro-pollutants and other contaminants caused by historic land and water use. Groundwater can be influenced by (historic and current) surface water quality through natural or artificial infiltration of surface water.	Monitoring and evaluation of water quality development. The impact of historical contaminations will proceed further into the groundwater system and cannot be undone, unless soil processes help to break down contaminants. Monitoring and evaluation are necessary to be able to timely respond to a changing water quality .	Measures to remove historical sources of pollution and to prevent new sources of pollution. Historical contaminations from past land use will affect the groundwater quality for a long period of time due to the low stream velocity of groundwater. Some historical point- pollutions may be removed through soil and groundwater remediation, but diffuse pollution cannot be removed. However, according to the water legislation in the European Water Framework Directive additional measures must be taken to reach the set goals on water quality protection in	Groundwater quality, nutrients, organic micro- pollutants, other contaminants, surface water quality, monitoring and evaluation, water legislation, water quality protection.
Population growth, industrial developments	Increasing sewage and wastewater discharges	Emerging contaminants in surface and groundwater require new drinking water treatment methods. Emerging contaminants, such as new industrial pollutants, medicine residues and micro plastics, may pose new threats to the groundwater and surface water guality, and consequently the raw	Enforcement of groundwater protection regulations on pollution incidents and monitoring and evaluation. Groundwater protection regulations on land and water use aim to reduce the risk of pollutions to avoid groundwater quality deterioration. This includes regulations for small incidents with point pollutions such as	2027. Development of treatment methods to remove emerging contaminants from sewage, industrial wastewater and/or drinking water. According to the water legislation in the European Water Framework Directive known sources of pollution must be reduced and new sources of pollution must be prevented. This may include prohibition by law or measures to reduce the use of specific chemical products.	Emerging contaminants, groundwater quality, surface water quality, resilience and reliability of the drinking water treatment, groundwater protection, land and water use, water legislation, sources of pollution, drinking water

Drivers	Pressure	Impact	Short-term response	Long-term response	Sustainability aspects
		water quality, especially when they cannot be removed using the currently available treatment methods. The changes limit the resilience and reliability of the drinking water treatment.	caused by a car accident to be reported and solved immediately by removing the source of pollution. Continuous enforcement of these regulations is essential. Monitoring and evaluation <u>areis</u> necessary to be able to timely respond to a changing water quality.	To deal with emerging contaminants it is essential to limit or remove the contaminant source . If all these measures fail, the contaminants must be removed by the drinking water treatment. Other or new drinking water treatment methods may be required. New treatment methods may cause an increase of energy use and environmental impact (excipients, wastewater, waste materials). This may lead to a higher drinking water tariff.	treatment methods, energy use, environmental impact, drinking water tariffs.
Population growth, industrial	Land use change	Land use (change) may cause groundwater quality deterioration.	Enforcement of groundwater protection regulations on land use change and monitoring and evaluation.	Combination of extensive land use functions with drinking water abstraction.	Land use change, groundwater quality, sources of pollution,
developments		Land use change may cause groundwater quality deterioration due to the risk of diffuse of point sources of pollution. The impact may be limited if land use changes towards less polluting land use functions.	Groundwater protection regulations on land and water use aim to reduce the risk of pollutions to avoid groundwater quality deterioration. This includes regulations on land use change developments. Continuous enforcement of these regulations is essential. Monitoring and evaluation is necessary to be able to timely respond to a changing water quality.	Combining extensive land use functions such as nature and sustainable agriculture with drinking water abstraction In local areas to reduce the groundwater quality deterioration rate, depending on the land use as well as hydrological and chemical characteristics of the water system .	groundwater protection regulations, water use, enforcement of regulations, monitoring and evaluation, drinking water abstraction, extensive land use, nature, agriculture, water system.
Changing climate variability, population	Surface water and groundwater quality	Surface water and groundwater quality deterioration determine the required drinking water treatment.	Monitoring of drinking water quality, in case of emergencies measures are taken to safeguard the drinking water quality.	Adjustment of treatment methods to be able to continue to meet the drinking water standards.	Raw water quality, drinking water standards, water quality, vulnerability of the water
population growth, industrial developments	quality deterioration	The raw water quality of the abstracted groundwater or surface water determines the treatment that is necessary to meet the legal drinking water standards. When water quality deteriorates in general, due to the vulnerability of the water system for contamination different and more complex treatment methods	The drinking water quality is constantly monitored and checked with drinking water standards. In case of drinking water quality emergencies local measures are taken, such as temporary boiling instructions to customers or temporary additional treatment, to safeguard the drinking water quality.	A deteriorating raw water quality may require adjustment of treatment methods to meet the drinking water standards and to ensure the resilience and reliability of the treatment . In general, a more complex treatment method leads to a higher energy use , and a higher environmental impact due to additional use of excipients, water loss and waste materials, which will lead to a higher drinking water tariff.	system for contamination, treatment methods, reliability and resilience of treatment, drinking water quality, emergencies, energy use, environmental impact, drinking water tariffs.

Drivers	Pressure	Impact	Short-term response	Long-term response	Sustainability aspects
		become necessary to ensure the reliability of the treatment to		If the raw water quality is under extreme pressure, adjustment of treatment methods	
		meet the drinking water standards.		may not be possible. This can ultimately lead	
		The resilience of the treatment		to the decision to close the local drinking	
		method or capacity may be		water abstraction and force the drinking water	
		insufficient to respond to		supplier to find and develop a replacing	
		variability in raw water quality.		abstraction location.	
Population	Incidental	Variations in raw water quality can	Monitoring and evaluation of water	Increase of resilience and reliability of drinking	Surface water quality,
growth,	changes in	only be handled if treatment	quality development.	water treatment.	groundwater quality,
industrial	surface water	method is resilient to these			resilience and reliability of
developments	and	variations.			the treatment, monitoring
	groundwater	Especially surface water quality	Monitoring and evaluation is	To handle a varying or deteriorating raw	and evaluation, raw water
	quality	can show strong water quality	necessary to be able to timely respond	water quality the resilience and reliability of	quality, energy use,
		variations. They can enforce	to a changing water quality.	the drinking water treatment must be	environmental impact,
		temporary interruption of the		extended. This may require innovations in	drinking water tariffs.
		surface water intake. Groundwater		treatment, which can lead to large	
		quality is more stable, and		investments, and higher energy use and an	
		therefore less vulnerable for		increase in environmental impact of the	
		incidental changes. However,		treatment. This may lead to a higher drinking	
		incidents can cause a permanent		water tariff.	
		change of groundwater quality. It			
		depends on the resilience and			
		reliability of the treatment			
		whether sudden variations in raw			
		water quality can be handled well.			

Appendix C Results <u>of</u> analysis case 3 "Drinking water demand growth"

Table C.1 Summary of impact, short-term and long-term response and sustainability *issueaspects* in case 3, "Drinking water demand growth" (for complete results of the case study see Table C.2).

Impact	Short-term response	Long-term response	Sustainability issue<u>aspect</u>s
A limited water resource availability will affect the drinking water availability.	See Table A.2.	See Table A.2.	Water resource availability, drinking water availability, resilience of drinking water supply, drinking water demand, water legislation.
A water quality deterioration affects the resilience and reliability of the drinking water treatment.	See Table B.2.	See Table B.2.	Water quality, drinking water treatment, reliability of treatment, drinking water standards.
A growing drinking water demand will put the reliability and resilience of the technical infrastructure under pressure.	See Table A.2.	Drinking water suppliers must adapt the technical infrastructure to the growing water demand. Water saving strategies may reduce the growth rate, which will limit the required extension of the technical infrastructure.	Drinking water demand, reliability of technical infrastructure, drinking water suppliers, drinking water availability, treatment, energy use, environmental impact, drinking water tariff.
A declining drinking water demand may also put the resilience of the technical infrastructure under pressure.	Research on potential risks of a decline in drinking water demand.	Adaptation strategies that increase the resilience of the infrastructure to growth as well as a decline of the drinking water demand.	Drinking water demand, reliability and resilience of technical infrastructure.

Table C.2 Results of analysis of Case 3 "Drinking water demand growth", where additional to the analysis of the first two cases. The (additional) sustainability <u>issueaspect</u>s in this case are displayed in bold. The grey cells refer to Table C.1.

Drivers	Pressure	Impact	Short-term response	Long-term response	Sustainability aspects
Changing climate variability, population growth, industrial	Limited water resource availability due to extreme weather	A limited water resource availability will affect the drinking water availability.	See Table A.2.	See Table A.2.	Water resource availability, drinking water availability, resilience of drinking water supply, drinking water demand, water legislation.
developments events, other water use or limited abstraction permits		A limited water resource availability will affect the drinking water availability. The abstraction permits may be insufficient to meet the drinking demand, and possibilities to extend the permits will be minimal. This will put the resilience of drinking water supply to respond to changes in drinking water demand under pressure. This may cause frequent exceedance of permit conditions, or failure to the drinking water legislation.	See Table A.2.	See Table A.2.	
Changing climate variability, population growth, industrial	Surface water and groundwater quality deterioration	A water quality deterioration affects the resilience and reliability of the drinking water treatment.	See Table B.2.	See Table B.2.	Water quality, drinking water treatment, reliability of treatment, drinking water standards.
developments		If the water quality deteriorates, this will affect the raw water quality of the water abstracted for drinking water production. The available drinking water treatment facilities may not be resilient to these changes. This affects the reliability of the water treatment, potentially causing exceedance of drinking water standards.	See Table B.2.	See Table B.2.	
Changing climate variability, population growth,	Growing drinking water demand	A growing drinking water demand will put the reliability and resilience of the technical infrastructure under pressure.	See Table A.2.	Drinking water suppliers must adapt the technical infrastructure to the growing water demand. Water saving strategies may reduce the growth rate, which will limit the required extension of the technical infrastructure.	Drinking water demand, reliability of technical infrastructure, drinking water suppliers, drinking water availability,

Drivers	Pressure	Impact	Short-term response	Long-term response	Sustainability aspects
industrial developments		The overall capacity of the technical infrastructure determines whether the supply is resilient to	See Table A.2	Depending on the effectiveness of the water saving strategies that are developed, the	treatment, energy use, environmental impact,
		respond to a higher drinking water demand . The drought in 2018 displayed technical limitations in		technical limitations must be solved to meet the growing drinking water demand . Drinking	drinking water tariffs.
		parts of the drinking water supply system, putting		water suppliers must solve the local aspects to	
		the reliability of the technical infrastructure under pressure		Because these adjustments take time, drinking	
				water suppliers must start solving the aspects	
				now. This requires substantial investments and	
				also lead to an increasing energy use and environmental impact, which may result in an	
				increasing drinking water tariff.	
Socio-	Decrease in	A declining drinking water demand may also put	Research on potential	Adaptation strategies that increase the	Drinking water demand,
economic	drinking water	the resilience of the technical infrastructure under	risks of a decline in	resilience of the infrastructure to growth as	reliability and resilience of
developments	demand	pressure.	demand.	demand.	technical infrastructure.
		If at some moment the socio-economic	While working on	The chosen adaptation strategies for a	
		developments reverse the drinking water demand	solutions for the	growing drinking water demand must also be	
		growth, the reliability and resilience of the	growing drinking	resilient and reliable under a decreasing	
		technical infrastructure will be put under pressure.	water demand, it is	drinking water demand.	
		Especially when the focus is on dealing with a	important to consider		
		growing water demand, there is the risk of over-	the potential risks of a		
		dimensioning of the technical infrastructure. This	decreasing demand.		
		will put the drinking water quality under pressure			
		in case of a decreasing drinking water demand .			

Appendix DSummary of Sustainable Development Goal 6 targets and indicators related tosustainability characteristics

Table D.1 Summary Sustainable Development Goal 6 targets and indicators related to sustainability characteristics

		Hydro	logical s	system	Tech	nical sy	stem	Socio-economic system		
Target	Indicator	Water quality	Water quality Water resource availability Impact of drinking water abstraction		Reliability of technical infrastructure	Resilience of technical infrastructure	Energy use and environmental impact	Drinking water availability	Water governance	Land and water use
6.1 By 2030, achieve universal and equitable access to safe and affordable drinking water for all	6.1.1 Proportion of population using safely managed drinking water services				x	x		x		
6.2 By 2030, achieve access to adequate and equitable sanitation and hygiene for all and end open defecation, paying special attention to the needs of women and girls and those in vulnerable situations	6.2.1 Proportion of population using safely managed sanitation services, including a hand-washing facility with soap and water									
6.3 By 2030, improve water quality by reducing pollution, eliminating dumping and minimizing release of hazardous chemicals and materials, halving the proportion of untreated wastewater and substantially increasing recycling and safe reuse globally	6.3.1 Proportion of wastewater safely treated6.3.2 Proportion of bodies of water with goodambient water quality	x x							x x	x x
6.4 By 2030, substantially increase water-use efficiency across all sectors and ensure sustainable withdrawals and supply of freshwater to address water scarcity and substantially reduce the number of people suffering from water scarcity	6.4.1 Change in water-use efficiency over time 6.4.2 Level of water stress: freshwater withdrawal as a proportion of available freshwater resources		x	x	x x	x	x x		x x	x x
6.5 By 2030, implement integrated water resources management at all levels, including through transboundary cooperation as appropriate	 6.5.1 Degree of integrated water resources management implementation (0–100) 6.5.2 Proportion of transboundary basin area with an operational arrangement for water cooperation 	x	x						x x	
6.6 By 2020, protect and restore water-related ecosystems, including mountains, forests, wetlands, rivers, aquifers and lakes	6.6.1 Change in the extent of water-related ecosystems over time			x					x	

		Hydrological system Water quality Water resource availability Impact of drinking water		ystem	Technical system		Socio-economic system			
Target	Indicator	Water quality	Water resource availability	Impact of drinking water abstraction	Reliability of technical infrastructure	Resilience of technical infrastructure	Energy use and environmental impact	Drinking water availability	Water governance	Land and water use
6.a By 2030, expand international cooperation and capacity-building support to developing countries in water and sanitation-related activities and programmes, including water harvesting, desalination, water efficiency, wastewater treatment, recycling and reuse technologies	6.a.1 Amount of water- and sanitation-related official development assistance that is part of a government coordinated spending plan								x	
6.b Support and strengthen the participation of local communities in improving water and sanitation management	6.b.1 Proportion of local administrative units with established and operational policies and procedures for participation of local communities in water and sanitation management								x	

Appendix E Overview of sustainability characteristics and criteria

Table <u>E.1</u>7 summarises the hydrological, technical and socio-economic sustainability characteristics and criteria for a local drinking water supply system from Tables 4-6<u>Section 3</u>.²

System	Sustainability characteristics	Sustainability criteria	General description	Sustainable	Under pressure	Unsustainable	Suggestions for general data sources	Reference for general data sources
		Current raw water quality Chemical aspects	To which extent does the current raw water quality meet set standards? Which trends are	Current raw water guality meets set standards Chemical water guality is	Occasionally the current raw water quality exceeds set standards Consistent chemical	Current raw water quality is permanently exceeding set standards Deteriorating chemical	e.g. Status of water bodies according to European Water Framework Directive Ibid	European Union (2000) Ibid
		of water quality	found in chemical water quality development?	improving	water quality	water quality		
	Motor quality	<u>Microbial aspects</u> of water quality	To which extent is microbial pollution a threat to the raw water quality?	No risk of microbial pollution	Microbial pollution is a potential risk, but the microbiological quality is sufficient	Microbial pollution is an actual risk and the microbiological quality is insufficient	Ibid	Ibid
<u>Hydrological</u> <u>system</u>	<u>water quaiity</u>	<u>Acceptability</u> aspects of water guality	Are there aspects of water quality that limit the acceptability of the drinking water (salinization, hardness, colour)?	<u>No issues with</u> acceptability of the drinking water	Salinization, hardness or colour cause a minor acceptability issue	Salinization, hardness and/or colour cause serious acceptability issues	Ibid	Ibid
		Monitoring and evaluation of water quality trends	Is there sufficient and adequate monitoring and evaluation of water quality trends available?	Sufficient and adequate monitoring and evaluation of water guality trends	There is monitoring available, but evaluation of data is limited, resulting in a limited understanding of water quality trends	There is limited or no monitoring available, and water quality trends are not investigated	Ibid	Ibid
	<u>Water resource</u> availability	<u>Surface water</u> <u>quantity</u>	Are there current limitations or future threats to the abstracted surface water volume?	Sufficient availability all year round or 'no surface water abstraction'	Surface water availability varies during the year and may occasionally be limited in case of dry weather conditions	There is regularly insufficient surface water volume available in the dry season	e.g. Status of water bodies according to European Water Framework Directive	European Union (2000)

² This appendix is an extended and updated version of appendix A of Van Engelenburg e.a. 2019

System	Sustainability characteristics	Sustainability criteria	General description	Sustainable	Under pressure	Unsustainable	Suggestions for general data sources	Reference for general data sources
		<u>Groundwater</u> <u>quantity</u>	Are there current limitations or future threats to the abstracted groundwater volume?	Abstraction is not limited because groundwater is recharged sufficiently (yearly abstraction <annual recharge minus environmental streamflow) or 'no groundwater abstraction'</annual 	Abstraction -is not limited but exceeds annual recharge minus environmental streamflow	Abstraction volume is limited because groundwater is abstracted from a confined aquifer that is not recharged ('mining')	e.g. Status of water bodies according to European Water Framework Directive	European Union (2000)
		<u>Other available</u> <u>water resources</u>	Are there water resources available for drinking water production other than currently used?	There are sufficient water resources available that could replace the current used water resource with minor adjustments to the drinking water treatment method	There are other water resources available that could replace the current used water resource, but this will require major adjustments to the drinking water treatment method	There are no water resources available that could replace the current used water resource	e.g. Status of water bodies according to European Water Framework Directive	European Union (2000)
		Vulnerability used water system for contamination	To which extent is the used water system vulnerable for contamination?	The water system is hardly vulnerable for contamination because the used water resource is protected by an aquitard (groundwater in confined aquifers)	The water system is vulnerable for soil and groundwater pollution (phreatic groundwater)	The water system is vulnerable for calamities and diffuse contamination (surface water)	<u>e.g. Status of water</u> <u>bodies according to</u> <u>European Water</u> <u>Framework Directive</u>	European Union (2000)
		<u>Natural hazards</u> and emergencies risk	To which extent are natural hazards (droughts, floods, earthquakes, forest fires) threatening the water resources availability?	Limited risk of natural hazards (<1 per 25 years)	<u>Minor risk of a natural</u> hazard (< 1 per 10 years)	Natural hazards occur frequently (> 1 per 10 years) and are a serious threat to water resources availability	e.g. National flood risk inventory, CSD Indicator of Sustainable Development (Percentage of population living in hazard prone areas)	UN (2007)
	Impact of drinking water abstraction	Impact to surface water system	The scale of impact of the abstraction to the surface water system	Small (groundwater abstraction below aquitard)	Medium (river bankriverbank abstraction, phreatic groundwater abstraction)	Large (surface water abstraction)	e.g. Status of water bodies according to European Water Framework Directive	European Union (2000)

System	Sustainability characteristics	Sustainability criteria	General description	Sustainable	Under pressure	Unsustainable	Suggestions for general data sources	Reference for general data sources
		Impact to groundwater system	The scale of impact of the abstraction to the groundwater system	Small (surface water abstraction)	Medium (river bankriverbank abstraction, groundwater abstraction below aquitard)	Large (phreatic groundwater abstraction)	<u>e.g. Groundwater</u> <u>footprint</u>	Gleeson and Wada (2013)
		Balance between annual recharge and abstraction	<u>The balance between</u> <u>abstraction and</u> <u>recharge of the water</u> <u>system</u>	The net abstraction volume is less than 10 % of the average annual recharge in the recharge area	The net abstraction volume is 10-40 % of the average annual recharge in the recharge area	The net abstraction volume is > 40 % of the average annual recharge in the recharge area	<u>SSI (Renewable water</u> resources)	Van der Kerk and Manuel (2008)
		<u>Hydrological</u> compensation	The extent to which the impact of abstraction is compensated hydrologically	Small impact or impact is hydrologically compensated with a technical measure	There are possibilities for hydrological compensation of the impact of the abstraction, but they are not operational yet	There is a significant impact of the abstraction, but there are no possibilities for hydrological compensation	<u>Local hydrological</u> <u>knowledge,</u> <u>hydrological modelling</u> <u>results</u>	<u>e.g.</u> Van Engelenburg et al. (2017), Van Engelenburg et al. (2020a)
		<u>Spatial impact of</u> <u>abstraction</u> <u>facility/</u> storage/reservoir	Size of required working area for abstraction facility	Small (groundwater abstraction with basic treatment facility)	<u>Medium (groundwater</u> <u>abstraction with</u> <u>medium treatment</u> facility)	Large (surface water abstraction with storage basins and extended treatment facility)	<u>Drinking water</u> company's information, map	-
		Technical state abstraction and treatment facility	Is the technical state of the drinking water production facility sufficient and fully deployable?	The technical state of the drinking water production facility is sufficient and fully deployable	Production capacity is sufficient but not fully deployable due to restrictions in permit or technical limitations	Production capacity is insufficient due to technical limitations	IWA (Ph1 Treatment plant utilisation)	Alegre et al. (2006b)
<u>Technical</u> <u>system</u>	<u>Reliability of</u> <u>technical</u> infrastructure	<u>Technical state</u> <u>distribution</u> infrastructure	Are there issues that complicate the drinking water distribution?	The distribution infrastructure is adequate to meet the required distribution capacity and water pressure	The distribution infrastructure is in general adequate but at extreme peak demand limitations in the drinking water distribution cause reduced water pressure and limited drinking water supply	The distribution infrastructure is insufficient and major disruptions of the drinking water supply occur regularly	<u>Performance data of</u> <u>water utilities</u>	<u>e.g. Dutch Drinking</u> Water Law (2009)

System	Sustainability characteristics	Sustainability criteria	General description	Sustainable	Under pressure	Unsustainable	Suggestions for general data sources	Reference for general data sources
		<u>Complexity of</u> water treatment	How complex is the required treatment and is the treatment effective to meet the water quality issues?	<u>Technical water quality</u> <u>issues (iron/manganese</u> <u>removal, pH-correction),</u> <u>require only basic</u> <u>treatment</u>	Water quality issues such as hardness require medium complex treatment (decalcification)	Serious water quality issues (chemical, microbiological) require a complex treatment (ultra-filtration, reversed osmosis)	<u>Performance data of</u> <u>water utilities</u>	<u>e.g. Dutch Drinking</u> <u>Water Law (2009)</u>
		Supply continuity for customers	Are there frequent drinking water supply interruptions?	<u>Drinking water supply</u> <u>interruptions < 1 hr per</u> <u>year</u>	<u>Drinking water supply</u> <u>interruptions < 10 days</u> <u>per year</u>	<u>Drinking water supply</u> <u>interruptions > 10 days</u> <u>per year</u>	Performance data of water utilities, IWA (QS17 Days with restrictions to water service)	Alegre et al. (2006b)
		<u>Operational</u> <u>reliability</u>	Is the facility operationally reliable?	Facility meets corporate standard for operational reliability	The facility does not fully meet corporate standard for operational reliability, but investments are planned to increase the operational reliability < 5 years	Facility is not operationally reliable and there are no investments planned to improve the reliability within 5 years	Performance data of water utilities	<u>e.g. Dutch Drinking</u> <u>Water Law (2009)</u>
		Abstraction permit compared to annual drinking water demand	Are the permitted abstraction volumes sufficient to meet the annual drinking water demand?	The permitted abstraction volumes are sufficient to meet the current and future annual drinking water demand (operational reserve > 10%)	The permitted abstraction volumes are sufficient to meet the current annual drinking water demand but cannot meet the future demand (operational reserve < 10%)	The permitted abstraction volumes are insufficient to meet the current of future annual drinking water demand	Performance data of water utilities	<u>e.g. Dutch Decree</u> on Water (2007)
	<u>Resilience of</u> <u>technical</u> infrastructure	Production capacity compared to peak demand	Is the production capacity per hour sufficient to meet extreme peak demand?	The production capacity per hour is sufficient to meet extreme peak demand	The production capacity is < 5% below the predicted extreme peak demand and therefore is not fully sufficient	The production capacity is > 5% below the predicted extreme peak demand and therefore is insufficient to meet peak demand	<u>Performance data of</u> <u>water utilities, IWA</u> (Ph1 Treatment Plant <u>Utilisation)</u>	Alegre et al. (2006b)
		<u>Flexibility of</u> <u>treatment method</u> <u>for changing raw</u> <u>water quality</u>	<u>Is the treatment</u> <u>method flexible to</u> <u>respond to a changing</u> <u>raw water quality?</u>	The treatment method removes a broad spectrum of pollutants and therefore can also handle various new pollutants- (e.g. membrane treatment methods)	The treatment method is flexible when concentrations of the currently removed elements change, but cannot remove other pollutants (e.g. decalcification)	The treatment method is not flexible to respond to large changes in concentrations or pollutants (e.g. sand filtration)	Performance data of water utilities	-

System	Sustainability characteristics	Sustainability criteria	General description	Sustainable	Under pressure	Unsustainable	Suggestions for general data sources	Reference for general data sources
		Technical innovations to improve resilience	Are technical innovations developed to improve resilience?	Within society there is an ongoing research to find technical innovations on drinking water use or supply to improve resilience	Within the drinking water company there is an ongoing research to find technical innovations for drinking water supply to improve resilience	There is no or limited research on technical innovations for drinking water supply	<u>Data of water utilities</u> (annual report)	-
		Technical investments to improve resilience	Are technical investments made to improve resilience?	Technical investments are made to improve the resilience of the drinking water infrastructure, including investments in technical innovations	There is a limited budget for technical investments to improve the resilience of the drinking water infrastructure	There is no budget for technical investments.	<u>Financial data of water</u> <u>utilities</u>	-
		<u>Energy use of</u> <u>abstraction and</u> <u>treatment</u>	Energy use for abstraction and treatment of water per <u>m3</u>	Low (shallow groundwater abstraction, short distance to treatment, basic treatment)	Average (deep groundwater abstraction, short distance to treatment, medium treatment groundwater)	<u>High (long transport</u> <u>distance to treatment,</u> <u>complex treatment)</u>	IWA Ph5 Standardised energy consumption	Alegre et al. (2006b)
		Energy use of distribution	Energy use for distribution	<u>Low (average transport</u> <u>distances < 15 km)</u>	Average (average transport distances < 30 km)	High (average transport distances > 30 km)	EBC (electricity use)	European Benchmarking Co- operation (2017)
	Energy use and environmental impact	Environmental impact (additional excipients, waste- water, waste materials)	Are there materials used or produced in the treatment with an environmental impact?	No use or produce of materials with high environmental impact	Use of additional excipients with high environmental impact in the treatment	Production of waste materials and wastewater with high environmental impact	EBC (climate footprint)	European Benchmarking Co- operation (2017)
		Reliability energy supply	<u>Is the energy supply</u> reliable?	<u>Reliable energy supply</u> and emergency energy backup	Average reliable energy supply, no emergency energy backup	<u>Unreliable energy</u> supply, no emergency <u>energy backup</u>	EBC (electricity use)	-
		<u>Use of renewable</u> <u>energy</u>	Use of renewable energy sources (own generation or acquired green energy)	<u>All used energy is</u> renewable energy	> 50 % renewable energy is used	< 50 % renewable energy	IWA Ph7 Energy recovery	Alegre et al. (2006b)
Socio-	Drinking water	Percentage connected households	Households directly connected to drinking water supply system	<u>> 95 %</u>	<u>80 - 95 %</u>	<u>< 80 %</u>	IWA QS3 Population coverage	Alegre et al. (2006b)
economic system	<u>prinking water</u> availability	Drinking water service quality	Continuity and quality of supply (local scale)	Continuity and quality of drinking water supply guaranteed 24/7	Continuity of drinking water supply or quality under pressure at peak demand	Drinking water quality and supply continuity not guaranteed	IWA QS12 Continuity of supply, QS18 Quality of supplied water	Alegre et al. (2006b)

System	Sustainability characteristics	Sustainability criteria	General description	Sustainable	Under pressure	Unsustainable	Suggestions for general data sources	Reference for general data sources
		<u>Drinking water</u> <u>tariff</u>	Average water charges without public charges (company scale)	<u><1€/m3</u>	<u>1 - 2 €/m3</u>	<u>>2€/m3</u>	IWA Fi28 Average water charges for direct consumption	Alegre et al. (2006b)
		<u>Water saving</u> <u>strategy</u>	Water saving strategy to reduce average water demand in litre per person per day (national scale)	Effective water saving strategy resulting in an average water demand < 100 pp pd	Water saving strategy aiming to reduce the average water demand of 100-200 l pp pd	No water saving strategy	SSI (Sufficient to drink)	Van der Kerk and Manuel (2008)
		<u>Water safety</u> protocols	Are there water safety protocols or water safety plans to safeguard the drinking water supply?	Water safety protocols fully cover the drinking water supply and the organisation is performing accordingly	There are safety protocols, but only covering a part of the drinking water supply of not fully performed	<u>There are no safety</u> protocols	Drinking water company's information	<u>e.g. Dutch Drinking</u> Water Law (2009)
		<u>Availability of</u> (drinking) water legislation and policies	Is there adequate legislation on drinking water supply and is there enforcement of this legislation?	<u>There is adequate</u> <u>legislation on drinking</u> <u>water supply combined</u> <u>with sufficient</u> <u>enforcement by- legal</u> authorities	<u>There is legislation on</u> <u>drinking water supply</u> <u>but limited or no</u> <u>enforcement by -legal</u> <u>authorities</u>	<u>There is no legislation</u> and enforcement on drinking water supply	SSI (Good Governance), national and local legislation	Van der Kerk and Manuel (2008)
		Compliance of drinking water supplier	Are the required permits available, and is the facility compliant to the permit requirements?	All permits are available, and the facility is compliant to the permit requirements	The permits are available, but the facility is not fully compliant to the permit requirements	There is a lack of adequate drinking water supply legislation and drinking water suppliers only follow their company's standard	SSI (Good Governance), permits, TRUST Framework for UWCS-sustainability (G1-G4)	Van der Kerk and Manuel (2008); Brattebø et al. (2013)
	<u>Water</u> governance	Decision-making process by (local) authorities	Are local stakeholders involved in decisions on drinking water supply or the water system?	Local stakeholders are involved in the planning process and can participate in licensing procedures	Local stakeholders are not involved in the planning process but cannot participate in licensing procedures	Local stakeholders cannot easily involve in the decision-making process	<u>SDG 6.b</u>	UN (2015)
		<u>Local stakeholder</u> interests	Does the local authority actively weigh stakeholder interests in the decision-making process?	Stakeholders are involved in the decision- making process and stakeholder interests must be taken into account in the licensing process legally	Stakeholder interests must be taken into account in in the licensing process	The interests of (some) local stakeholders are not accounted for by the local authorities	SDG 6.b, national or local legislation	<u>UN, 2015</u>
		Emergency risk caused by human activities or conflicts	Is there emergency risk caused by human activities or conflicts?	There is in general no serious emergency risk caused by human activities or conflicts	<u>There is a low</u> <u>emergency risk caused</u> <u>by human activities</u>	<u>There is an evident</u> <u>emergency risk caused</u> <u>by human activities or</u> <u>conflicts</u>	<u>SDG 16</u>	<u>UN, 2015</u>

System	Sustainability characteristics	Sustainability criteria	General description	Sustainable	Under pressure	Unsustainable	Suggestions for general data sources	Reference for general data sources
		<u>Land use</u> (including subsurface use)	Is land or subsurface use in the area posing a threat to the drinking water supply?	The impact of land or subsurface use is limited due to low-risk use or because the drinking water supply is well protected against the impact	The land or subsurface use forms a potential risk to the drinking water supply but is regulated	The land or subsurface use is affecting the drinking water supply	<u>e.g. Status of water</u> <u>bodies according to</u> <u>European Water</u> <u>Framework Directive</u>	<u>European Union</u> (2000)
		Water use for other purposes than drinking water	Doests water use in the area poseing a threat to the drinking water supply?	In general, there is sufficient water available for all functions and water quality is not affected by water use	In extreme situations the available water resources are limited and must be fairly distributed between water users, or water guality deteriorates	There is constantly insufficient water available for all water users and/or water quality deterioration due to various water use	e.g. Status of water bodies according to European Water Framework Directive	<u>European Union</u> (2000)
	<u>Land and water</u> <u>use</u>	Regulations on land and water use	Are there regulations on land use and underground activities to protect the local drinking water abstraction?	There are regulations to remove unwanted activities from the recharge area to protect the local drinking water abstraction	There are regulations to prevent new unwanted activities by using the stand- still/step forward principle	There are no regulations to protect the local drinking water abstraction	(Inter)national legislation, TRUST Framework for UWCS- sustainability (G1-G4)	<u>e.g. Dutch Decree</u> on Water (2007), Brattebø et al. (2013)
		Limitations to land or water use	Is the presence of the facility a significant impediment for current or future land use of underground activities?	The drinking water supply does not present a significant impediment for land or subsurface use	The drinking water supply limits future land use or underground activities	The drinking water supply is a significant impediment for current as well as future land use or underground activities	e.g. Status of water bodies according to European Water Framework Directive	<u>European Union</u> (2000)
		<u>Financial</u> <u>compensation of</u> <u>economic damage</u> <u>from impact of</u> <u>abstraction or</u> <u>limitations to land</u> use	Is there financial compensation of economic damage from the impact of abstraction or limitations to land use?	Financial compensation of economic damage caused by the drinking water supply is organised based on legislation	Drinking water suppliers financially compensate economic damage based on bilateral agreements	There is financial compensation of economic damage caused by the drinking water supply company	<u>National or local</u> legislation	<u>e.g. Dutch Decree</u> <u>on Water (2007)</u>